NOTICE TO WATER WELL CONTRACTOR The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELLKEGE IVED

STATE OF OREGONGS

(Please type or The Company of the Compan

State	Well	Νo.	375	/2w	- 33
2000	.,	_,,,	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		

STATE OF OREGONUG8 1975 State Well No. 375

(Please type or print)
WATER RESOURCES DEPEtate Permit No. _____
(Do not write above this line)
SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:		
Name Western Carriage Estates	County Jackson Driller's well number		
Address 3455 Stage mis Modford	SE 16 SE 16 Section 38 T375 R2W W.M.		
Maltad Dle			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner		
New Well Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	- · · · · · · · · · · · · · · · · · · ·		
	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found /10 ft/		
Rotary Driven Domestic Industrial Municipal	Static level 25 ft. below land surface. Date \$1477		
Cable	Artesian pressure lbs. per square inch. Date		
	and product men. Date		
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing		
"Diam. fromft. toft. Gage _,250	Depth drilled 300 ft. Depth of completed well 300 ft.		
" Diam. from ft. to ft. Gage			
ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
A properties	with at least one entry for each change of formation. Report each change in		
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	Brown clay 0 55		
perforations from ft. to ft.	Growel molium, 55 61		
perforations from	Gravel, brown clay heary 6/ 70		
perforations from ft. to ft.	Shale hard, analigoot 70 300 25		
(7) SCREENS: Well screen installed? Yes No			
Manufacturer's Name			
Type Model No			
Diam Slot size Set from ft. to ft.			
Diam. Slot size Set fromft. toft.			
(9) WELL TESTS. Drawdown is amount water level is			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes 16 Ves, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " "	The same of the sa		
" " " "			
Ail			
Batter test 40 gal./min. with 225 ft. drawdown after 4 hrs.			
Artesian flow g.p.m.			
reperature of water Depth artesian flow encountered ft.	Work started 7/30 125 Completed 8/4 19/5		
-	Date well drilling machine moved off of well 8/4 1975		
(9) CONSTRUCTION:	The west database materials and west of the state of the		
Well seal-Material used Coment grout	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore to bottom of seal in.	best knowledge and belief.		
Diameter of well bore below seal in.	[Signed] 1881 Zasut Date 8/5 19/5		
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		
Brand name of bentonite	Weden Well Control of the U.S.		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? Yes No Plus Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water? Yes 100	Name (Person, firm or corporation) (Targe or print)		
The of streets	Address 14 Milain rd. Grant Bes Orp		
Lype of water.	Tarkall 1		
Method of sealing strata off	[Signed] Wayshan		
Was well gravel packed? ☐ Yes ☐ 10 Size of gravel:	(Water Well Contractor)		
Gravel placed fromft.	Contractor's License No. 4 Date Date 195		
- Control of the Cont			