

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON, 97310

within 30 days from the date of well completion.

RECEIVED APR 17 1969

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line)

RECEIVED MAY 2 1969 STATE ENGINEER SALEM OREGON

JACK 13825

State Well No. 37/ZW-34

State Permit No.

(1) OWNER:

Name W. S. Ferris Address 3859 Bellinger Lane, Medford, Ore.

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

6" Diam. from 0 ft. to 63 ft. Gage 250. Threaded [] Welded [X]

PERFORATIONS:

Type of perforator used Torch Size of perforations 1 in. by 8 in. 3x10-30 perforations from 30 ft. to 63 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 5 ft. below land surface Date 3/17/69 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [X] Yes [] No If yes by whom? SHIYOU PUMP Yield: 6 gal./min. with 14.5 ft. drawdown after 16 hrs. Baller test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date Temperature of water 58 Was a chemical analysis made? [] Yes [X] No

(10) CONSTRUCTION:

Well seal—Material used bentonite Depth of seal 20' Diameter of well bore to bottom of seal 9 1/2 in. Were any loose strata cemented off? [X] Yes [] No Depth Was a drive shoe used? [X] Yes [] No Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [X] Yes [] No Size of gravel: 3/8" Gravel placed from 20 ft. to 61 ft.

(11) LOCATION OF WELL:

County Jackson Driller's well number #3 SE 1/4 NW 1/4 Section 34 T. 37 R. 2W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 6" Depth drilled 150 ft. Depth of completed well 150 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include: dark br. top soil clay, br. clay with sm. gravel, br. clay & gravel, br. clay, gravel & boulders, gravel, boulders, sand, grey hard rock.

Work started 3/11/69 19 Completed 3/17/69 19 Date well drilling machine moved off of well 3/17/69 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] D. Hadeau Date 3/30/69 (Drilling Machine Operator)

Drilling Machine Operator's License No. 635

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Rotary Drilling Co. (Person, firm or corporation) (Type or print)

Address 1044 W. 12th, Medford, Ore. 97501

[Signed] [Signature] (Water Well Contractor)

Contractor's License No. 338 Date 3/30/69, 19

11/17/74

11/17/74

11/17/74

11/17/74