NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this in the large of the state of the lied with the large of the large o

SALEM, OREGON 97310 within 30 days from the date

OCT 1 3 1977 (Please type or print)

we.	<u>K</u>		/
751	State Well	No. 375/2	40-32
1440.	State Permi	it No	

of well completion. WATER RESOURCE'S DEPT.	ove this line)		
(1) OWNER: SALEM, OREGON	(10) LQCATION OF WELL:		
	County Driller's well number		
Address 7 5 Sign Ref Re Co.	1/4 1/4 Section 3 2 T. 37 S. 4W W.M.		
GERAR PASS OF 07526	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	bearing and distance from security of substitution society		
New Well			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 55 ft.		
Rotary Driven Domestic Industrial Municipal	Static level 7 5 ft. below land surface. Date/6-6-7)		
Cable	Artesian pressure lbs. per square inch. Date		
	Artesian pressure ibs. per square men. Date		
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing		
"Diam. from 4 ft. to 31 ft. Gage 1250	Depth drilled 125 ft. Depth of completed well 125 ft.		
ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;		
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,		
PERFORATIONS: Perforated?   Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	1 0 (max		
perforations from	CLAY SANOY BROWN, 1 5		
perforations from ft. to ft.	CLAY BOMEDRAS BROWN 5-12		
perforations from ft. to ft.	CLAY BROWN 12 23		
	JAMSDNE GRAY 23 28		
(7) SCREENS: Well screen installed?   Yes   No	GLANITE VECOMINSED BLOWN 28 56		
Manufacturer's Name	GRAMITE BLOCES) BROWN 56 57 35		
Type Model No	BASOL SENSON SILE 109 130 22		
Diam. Slot size Set from ft. to ft.	BASALT DROKEN SURE 104 120 22		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level  Was a pump test made?   Yes To If yes, by whom?			
ald: gal/min. with ft. drawdown after hrs.			
n n n	7.2 -		
sailer test 150 gal./min. with 98t. drawdown after hrs.	<u> </u>		
nperature of water Depth artesian flow encounteredft.			
nperature of water Depth artesian flow encountered ft.	Work started / O-5 19/ Completed / O-6 19/		
(9) CONSTRUCTION:	Date well drilling machine moved off of well /0-6 19/		
Well seal-Material used CEmEan	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my		
Diameter of well bore to bottom of sealin.	best knowledge and belief.		
Diameter of well bore below sealin.	[Signed] Date (0.70, 19)		
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)  Drilling Machine Operator's License No.		
How was cement grout placed? TESSINE 6 COLL			
Acw Bossen Or	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? Thes I No Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water?   Yes No	Name (Person, firm or corporation) (Type or print)		
	Address 1923 Delta Waters Wall		
	rel 1) Le Lia		
Method of sealing strata off	[Signed] (Water Well Contractor)		
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)  Contractor's License No. 545 Date		
Gravel placed fromft_ toft_	Contractor's License No. 3.48 Date		