WATER WELL REPORT STATE OF OREGON

RECEIVED

EUG 8 1985

WATER RESOURCES DEPT SALEM, CREGON

JACK	_ √State Well No.	38=/1W-15cb	,
14834	State Permit No	Jo	

(1) OWNER: Name Farmers Market	(10) LOCATION OF WELL: County Jackson Driller's well not	
Address 4880 South Pacific Hwy.	OC	1
City Phoenix 97535 State Ore	NW ½ SW ½ Section 15 T. 38 R. Tax Lot # 300 Lot Blk	***************************************
	Address at well location: Same as # 1	Subdivision
(2) TYPE OF WORK (check):	TRACES AT WELL RECEIPED. Scales Cas // L	
New Well 🖔 Deepening 🗆 Reconditioning 🗆 Abandon 🗆	(11) WARRIED FRANCE OF THE P	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well	•
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 97	
X	Static level 33 ft. below land	
Rotary Mud	Artesian pressure lbs. per sq	uare inch. Date
☐ Bored ☐ Thermal: .:. Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below casi	ng
(5) CASING INSTALLED: Steel X Plastic	Depth drilled 260 ft. Depth of com	pleted well 260 ft.
Threaded Welded	Formation: Describe color, texture, grain size and structu	re of materials; and show
6 "Diam. from +1 ft. to 39 ft. Gauge .250	thickness and nature of each stratum and aquifer penetrat for each change of formation. Report each change in posi-	ed, with at least one entry
"Diam. from	and indicate principal water-bearing strata.	NOTI OF SOURCE WATER LEVEL
LINER INSTALLED:	MATERIAL F	rom To SWL
		0 3
(A) DEDECT ATTOM		3 26
(6) PERFORATIONS: Perforated? □ Yes № No	Gravel Mixed	
Type of perforator used	1	
Size of perforations in. by in.	— Claystone Gray 3	1 260 33
perforations from		
perforations from ft. to ft.		
perforations from ft. to ft.		
(7) SCREENS: Well screen installed? ☐ Yes ☑ No		
Manufacturer's Name		
Type Model No.		
Diam. Slot Size Set from ft. to ft.		
Diam. Slot Size from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes ☐ No If yes, by whom?		
d: gal./min. with ft. drawdown after hrs.		
11 " " "		
Air test 8 gal./min. with drill stem at $260_{\text{ft.}}$ $1\frac{\pm}{2}$ hrs.		
Bailer test gal./min. with ft. drawdown after hrs.		
Autesian flow g.p.m.		
perature of water 56 Depth artesian flow encounteredft.	Work started 7/23 19 85 Completed	7/23 ₁₉ 85
(9) CONSTRUCTION: Special standards: Yes \(\text{No } \frac{\text{Y}}{\text{T}} \)	Date well drilling machine moved off of well 7/23	19 85
Well seal—Material used .Cement.		1907
Well sealed from land surface to38ft	Drilling Machine Operator's Certification:	
Diameter of well bore to bottom of seal10 in.	This well was constructed under my direct supe and information reported above are true to my best	rvision. Materials used knowledge and belief
Diameter of well bore below seal		
Number of sacks of cement used in well seal	(Drilling Machine Operator)	
How was cement grout placed? Pressure Pumped	Drilling Machine Operator's License No483	***************************************
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction an	d this report is true to
Was pump installed?	the best of my knowledge and belief.	
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name Gribble Well Drilling	(Type or print)
Did any strata contain unusable water? Yes You	(Person, firm or corporation) Address 195 Country Lame Gold H	ill Ore
Type of Water? depth of straua	l. auth.	· · · · · · · · · · · · · · · · · · ·
Method of sealing strata off	[Signed] (Water Well Contractor)	•
Was well gravel packed? ☐ Yes ☐ Wo Size of gravel:	Contractor's License No. 705 Date 7/28	, 85
Gravel placed from ft. to ft.	Date	,, 1 y