NOTICE TO WATER WELL CONTRACTOR ,The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

TAC	K 22/
171850	State Well No. 38/10-/5 CC
1700-	State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Mr. & Mrs. Jeff Edmondson	county Jackson Driller's well number 80-79
Address 5126 S. Pac. Hwy.	SW 1/4 SW 1/4 Section 15 T. 38 R. 1W W.M.
Phoenix, Ore. 97535	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Tax lot #3601
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	new
Rotary Driven Demostic W Industrial D Musicial	
The Period III	Static level 15'4" ft. below land surface. Date 7/28/80
	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded  welded  Gage .250	(12) WELL LOG: Diameter of well below cosing 6
5 CASING INSTALLED: Threaded □ Welded □ +1 6" ft. to +1 6" ft. Gage 250	Diameter of wen below casing
" Diam. from ft. to ft. Gage	Depth drilled 756 ft. Depth of completed well 156 ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
(6) PERFORATIONS: Perforated? The Company of the Co	with at least one entry for each change of formation. Report each change in
Totalated 12 Tes 11 No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Skillsaw  Street perforations 1/8 in the 8	MATERIAL From To SWL
bize of periorations , in, by in.	Claystone grey some gr- 46 52 15'4"
117 perforations from 95 ft. to 155 ft.	avel embedded
20 perforations from 20 ft. to 95 ft.	Claystone 30%sandstone 52 138
perforations from ft. to ft.	30%shale 35%all grey
(7) SCREENS: Well screen installed?   Yes   No	5%brown siltstone all
Manufacturer's Name	layered
Type Model No	Sandstone grey very hard 138 141 15'4"
Diam. Slot size Set from ft. to ft.	Shale grey mild 141 144
Diam. Slot size Set from ft. to ft.	Sandstone grey hard 144 156 15'4"
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
s a pump test made? [ Yes   No If yes, by whom? ]riller	
Viold: 15	
gai./min. with 140 ft. drawdown after 1 hrs.	SEP 0 5 1980
". ""	WATER RESOURCES DEPT
ler test gal./min. with ft. drawdown after hrs.	SALEM, OREGON
Artesian flow g.p.m.	
Temperature of water 59 Depth artesian flow encountered ft.	Work started 7/28 1980 Completed 7/30 180
(9) CONSTRUCTION:	Date well drilling machine moved off of well 7/30 180
Well seal-Material used added 2' steel casing to	Drilling Machine Operator's Certification:
Well sealed from land surface to bring above ground ft	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal level and, added	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal lecement grout	
Number of sacks of cement used in well seal	[Signed] (Drilling Machine Operator) Date 9/3, 1980.
How was cement grout placed?	Drilling/Machine Operator's License No. 1380
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief,
Did any strata contain unusable water? 🔲 Yes 🕝 No	Name J & J Well Drilling  (Person, firm or corporation) (Type or print)
Type of water? potable depth of strata	- ' '
Method of sealing strata off	Address B.O. Box 465 Talent, Or 97540
	[Signed] fish of husbendel
Was well gravel packed? ☐ Yes ▼No Size of gravel:	(Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 763 Date 9/3 1980