NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMER FECEIVERADE OF	LL REPORT	20-12	2/
WATER RESOURCES DEPARTMENT LUCIV Frame of SALEM, OREGON 97310 within 30 days from the date of well completion. FEB21 1979		<u>385/2u</u> 10	
WATER RESOURCES DEPT.	above this line)		
(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:		
Name Rogue River Junior Academy		600	
Address 3675 South Stage Road			
Medford, OR 97501	NE 34 NW 34 Section 3 T. 38 R. 2W W.M.		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner		
New Well XX Deepening [] Reconditioning [] Abandon []	<u>Tax Lot 5800</u> Permit 36-79w		·
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	- (11) WATER LEVEL: Completed well. Depth at which water was first found 50 ft.		
Rotary XX Driven Cable Jetted Domestic XX Industrial		surface. Date 2/	
Dug Bored Irrigation Test Well Other			5,17
CASING INSTALLED	IDS. per squa	re inch. Date	
Thicaded) welded kik	(12) WELL LOG: Diameter of well	holow enging	6
<u>6</u> "Diam. from <u>0</u> ft. to <u>40</u> ft. Gage •250	Depth drilled 250 ft. Depth of comp		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size		
	and snow thickness and nature of each stratu	m and aquifer ne	matratad
PERFORATIONS: Perforated? Yes XX No.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion Report anal	abanas in
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Shale, brown	0 19	
	Shale, black	19 24	
perforations from ft. to ft.	Shale, black fractured	24 33	
perforations from ft. to ft.	Shale, black	33 50	
(7) SCREENS: Well surgen installed?	Shale, black w/fractures	50 74	
Monufacture News	Rock, gray hard w/fractures	74 190	
Manufacturer's Name	Shale, black w/fractures	190 250	30
Type Model No. Diam. Slot size Set from ft. to ft.			
Diam. Site size Set from ft. to ft. Diam. Slot size Set from ft. to ft.			
IL to	Manual 1997		······
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes XXNo If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
n n n n n n n n n n n n n n n n n n n			
Air, " " " "			
RAMEX test & gal./min. with 210 ft. drawdown after 1 hrs.			
Artesian flow g.p.m.			
emperature of water 52 Depth artesian flow encountered ft.			
Y	Work started 2/1 1979 Complete		19 79
(\$, CONSTRUCTION:	Date well drilling machine moved off of well	2/5	₁₉ 79
Well seal-Material used Cement Grout	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my	direct super-	vision.
Diameter of well bore to bottom of seal10in.	Materials used and information reported best knowledge and belief	above are true	to my
Diameter of well bore below seal6 in.	sain in Nakort (hausting in	Date 2/8	1.79
Number of sacks of cement used in well seal	(Drilling Machine Operator)		
How was cement grout placed?	Drilling Machine Operator's License No	809	***********
Grout pump and drop pipe.	Water Well Contractor's Certification:		
	This well was drilled under my jurisdi	ction and this re	nort ie
Was a drive shoe used? 🖾 💥 es 🗍 No Plugs	true to the best of my knowledge and belief.		
Did any strata contain unusable water? 🗍 Yes 🖾 XNo	Name McClanahan Well Drilling		
	(Person, firm or corporation) 141, NE Beacon Drive Gr	(Type or prin ants Pass.	DR
supplied of sugara	Address 141 12 Beacon Drive Gr		 7
Method of sealing strata off	[Signed] Alange H. M.C	EV Anna l.	
Was well gravel packed? 🗌 Yes 🎇 No 🔔 Size of gravel:	(Water Well Contra	ctor)	
Gravel placed from ft. to ft.	Contractor's License No Date	2110mm 8	10 79
(USE ADDITIONAL SH			45858_110