WATER WELL REPORT
STATE OF OREGON

Per WWC #12 - Date was moved 5/27 + date finished 5/27 cw 6/1/83

RECEIVED
JUN 1 1983
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 38S/2W-32cd

State Permit No. Jack 16909

(1) OWNER:
Name Mr. Ludwig
Address 5758 Sterling Ck.
City Jacksonville State Ore.

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary Air ☐ Driven ☐
Rotary Mud ☐ Dug ☐
Cable ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: Withdrawal ☐ Reinjection ☐

(5) CASING INSTALLED:
Steel ☐ Plastic ☐
Threaded ☐ Welded ☑
6" Diam. from +2 ft. to 18 ft. Gauge .025
" Diam. from ft. to ft. Gauge

LINER INSTALLED:
" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:
Perforated? ☐ Yes ☑ No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☑ No If yes, by whom?
Yield gal./min. with ft. drawdown after hrs.
" " "
Air test 20 gal./min. with drill stem at 37 ft. 1 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 52° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Special standards: Yes ☐ No ☑
Well seal—Material used cement grout
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 8 sacks
How was cement grout placed? grout pump
Was pump installed? Type HP Depth ft.
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Jackson Driller's well number
SE ¼ SW ¼ Section 32 T. 38S R. 2W W.M.
Tax Lot # 500 Lot Blk Subdivision
Address at well location: 5758 Sterling Ck. Jacksonville, Oregon

(11) WATER LEVEL: Completed well.
Depth at which water was first found 27 ft.
Static level 15 ft. below land surface. Date 5/27/83
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6"
Depth drilled 60 ft. Depth of completed well 60 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brown clay	0	15	15
Black shale	15	20	
Gray shale	20	30	
Black shale w/fracture	30	60	

Work started 5/27 1983 Completed 5/27 1983
Date well drilling machine moved off of well 5/ 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Charles B. Kelley (Drilling Machine Operator) Date 5/27, 1983
Drilling Machine Operator's License No.

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name McClanahan Well Drilling (Person, firm or corporation) (Type or print)
Address 141 NE Beacon Dr. GPO.
[Signed] Ken McClanahan (Water Well Contractor)
Contractor's License No. Date, 19

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*12658-690