NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date

JACK 17244

WATER WELL REPORT TIVE 1244 STATE OF OREGON MAY 25 1973 State Well No. 385 366-27

of well completion. (Do not write a	BOVERNAME ENGINERATE ENGINERATE PERMIT	No	
(1) OWNER: R. C. C.	(10) LOCATION OF WELL:		
Address 2/ Adala St. 100. O. St. 110.	County Driller's well number SN 14 N E 14 Section 27 T 385 R. 3 W.M.		
STORY CONTRACTOR OF THE			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivis	sion corner	
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) THATTED I DYNEY C. I. I.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed y	vell. 207	
Potony TA Drivon D	Depth at which water was first found ft.		
Cable	Static level	surface. Date 3-3/-/3	
Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded Welded 50 50 Threaded Welded 50 50 Threaded Case 50 50 Threaded Welded Threaded Welded Threaded Welded Threaded Welded Threaded Threaded Threaded Threaded Welded Threaded Threaded	(12) WELL LOG: Diameter of well pepth drilled / 26 ft. Depth of comp	190	
	Formation: Describe color, texture, grain size	and structure of materials:	
ft. to ft. Gage	and show thickness and nature of each stratu	ım and aquifer penetrated,	
PERFORATIONS: Perforated? Yes Ye	with at least one entry for each change of format position of Static Water Level and indicate principle.		
Type of perforator used	MATERIAL.	From To SWL	
Size of perforations in. by in.	Rose De de Sel Lite	10) 72	
perforations from ft. to ft.	Word Court of Chemistre		
perforations from ft. to ft.	Memporal Brank	93 62	
perforations from ft. to ft.	- Carrigate Doger		
(7) SCREENS: Well screen installed? Yes No	Frostural Bossot	6274	
Manufacturer's Name	May Bankt	711 97	
Type Model No	Jesus .	17 10	
Diam Slot size Set from ft. to ft.	Martined Basilt	92 /07	
Diam Slot size Set from ft. to ft.	Water Black		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Boult	102/26	
Was a pump test made? ☐ Yes DNo If yes, by whom?			
gal./min. with ft. drawdown after hrs.			
" " "			
#3 ¢ " " " "		 	
gal./min. with $\frac{1}{2}$ ft. drawdown after / hrs.		 	
sian flow g.p.m.		 	
inperature of water Depth artesian flow encountered			
Depth artesian now encountered It.	Work started 5 - /4 19/3 Complete	ted 5 - 1973	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	S ~ 2/ 19/3	
Well seal-Material used	Drilling Machine Operator's Certification	:	
Well sealed from land surface toft.	This well was constructed under my Materials used and internation reported	direct supervision.	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	_	
Diameter of well bore below seal	[Signed] [Signed] Date 5-33, 19 27		
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.		
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	liction and this Paport is	
of waterlbs./100 gals.	true to the best of my knowledge and belief.		
Was a drive shoe used? Lives \(\subseteq No Plugs	Name Cyco-M Cfallsky K	cerneurs	
Did any strata contain unusable water? Yes No	Address (Person, firm or corporation)	O Hear Port	
Type of water? depth of strata	Address 130 Miles (MCA)	T. Caragina Vot	
Method of sealing strata off	[Signed] Louge III Cla	MIKERON	
Was well gravel packed? ☐ Yes I No Size of gravel:	(Water Well'Cont		
Gravel placed from ft. to ft.	Contractor's License No. 22 Date	5-33 _{,19} 23	