NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED JUL 16 1971 STATE ENGINEER SALEM, OREGON

JACK 17260

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

Jack 17260

State Well No. 38/3W-27

State Permit No.

(1) OWNER:
Name Newton Ward
Address Rt. 1 Box 2591
Florence, Ore. 97439

(2) TYPE OF WORK (check):
New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ]
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary [X] Driven [ ]
Cable [ ] Jetted [ ]
Dug [ ] Bored [ ]

(4) PROPOSED USE (check):
Domestic [X] Industrial [ ] Municipal [ ]
Irrigation [ ] Test Well [ ] Other [ ]

) CASING INSTALLED: Threaded [ ] Welded [X]
6" Diam. from 0 ft. to 57 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

) PERFORATIONS: Perforated? [ ] Yes [X] No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? [ ] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? [X] Yes [ ] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
AIR
Bailer test 4 gal./min. with 119 ft. drawdown after 2 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Bentonite
Well sealed from land surface to 57 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 30 lbs. sacks
Brand name of bentonite National
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [ ] Yes [X] No Plugs Size: location ft.
Did any strata contain unusable water? [ ] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [ ] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Jackson Driller's well number
¼ ¼ Section 27 T. 38S R. 3W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 62 ft.
Static level 5 ft. below land surface. Date 6/17/71
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 124 ft. Depth of completed well 124 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Soil--brown	0	8	
Clay & shatterd rock.br.	8	51	
Conglomerate---grey	51	69	
" brown	69	71	
" grey	71	86	
" brown	86	87	
" grey	87	124	

Work started 6/16 1971 Completed 6/17 1971
Date well drilling machine moved off of well 6/17 1971

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Geo. Mikkonen (Drilling Machine Operator) Date 6/18, 1971
Drilling Machine Operator's License No. 483

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Goff Brothers Well Drillers (Person, firm or corporation) (Type or print)
Address 1645 Springbrook Rd., Medford, Ore.
[Signed] (Water Well Contractor)
Contractor's License No. 175 Date 6/18, 1971

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119