NOTICE TO WATER WELL CONTRACTOR TO WATER WELL CONTROL The original and first copy of this report are to be filed with the

Was well gravel packed? ☐ Yes ☑ No

Gravel placed from ..

JACK 17261

WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 97310 V 16 1970 Process type or print) within 30 days from the State A Town 15 1970 Process type or print)

State Well No.

of well completion. SALEM (Do not write at	ove this line)	0	***************	Pościewania powerza .
SALEM ORLGON (1) OWNER:	(10) LOCATION OF WELL:			
Name Westward-Ho Const.	County Jorkson Driller's well number			
Name NEST WAYA - FTO CONST.				
Address 264 Pitty igni Breson	34 14 Section 27 T. 38 R. 310 W.M.			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi			
	20 cast from the north west			
New Well Deepening Reconditioning Abandon Reconditioning	property corner			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 33 ft.			
Rotary Driven Domestic Industrial Municipal Domestic Industrial Do	Static level 59 ft. below land	surface.	Date //	<u>-9-20</u>
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per squar	e inch.	Date	
CASING INSTALLED: Threaded Welded Threaded Threa	(12) WELL LOG: Diameter of well		_	6
" Diam. fromft. toft. Gage	Depth drilled 20 ft. Depth of comp			<u>O</u> ft.
	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	and struc	ture of r	naterials;
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Rep	ort each	change in
PERFORATIONS: Perforated? Yes No.	MATERIAL	From	То	swL
Size of perforations in. by in.	Soil- Grown	710.11	2	SWD
perforations fromft. toft.	Clar- Grown_	2	70	
perforations from ft. to ft.	Basalt - 6/40	20	23	-
perforations fromft. toft.	basalt - broken	87.3	825	59
peraduction if the contract of	basalt-6/4e	85	112	
(7) SCREENS: Well screen installed? Yes No	BASALT-LUCKER	117	113	59
Manufacturer's Name	basalt-blue	1/2	120	<u> </u>
TypeModel No	CCSCI V SIRE	11.5	1000	
Diam, ft. to ft.				
Diam Slot size Set from ft. to ft.				 -
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? 🔲 Yes 💋 No If yes, by whom?			,,	
Yield: gal./min. with ft. drawdown after hrs.				
n n n				
" " "				
JET1/		<u> </u>		
test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m.	~ @		· ·	
Artesian flow g.p.m. Lemperature of water Depth artesian flow encounteredft.				
	Work started // 9 19 20 Complete Date well drilling machine moved off of well	3d //	<u>-Σ'</u>	1920
CONSTRUCTION:			<u>- 7</u>	19/0
Well seal-Material used Bentonite	Drilling Machine Operator's Certification:			-
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	above :	super are true	vision.
Diameter of well bore to bottom of seal in.	best knowledge and belief.		_	·
Diameter of well bore below seal in.	[Signed] (Drilling Machine Operator)	Bate 🏒	/-9	., 1920
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	.34	45	-
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's License 100.		<i></i>	
Brand name of bentonite Wyo-Be	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is			
of water lbs./100 gals.	true to the best of my knowledge and bel	ief.		ebore 18
Was a drive shoe used? Yes And Plugs Size: location ft.	Name Charlet Well Dullins	· Za	1C	*************
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	. S	pe or pri	nt)
Type of water? depth of strata	Address / January 13		MA	LOLC
Method of sealing strata off	[Signed] [Chillips	\geq	~	
Was well gravel packed? Tyes Was No Size of gravel:	(Water Well Cont	actor)		

Contractor's License No. 83 Date

Size of gravel: