NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT C TATE OF OREGON
SALEM, OREGON 97310
within 30 days from the date
of well completion.

State Well No. ..

385/4W-8

State Permit No.

. AUG 31977 Wille 21	ove and me,			
(1) OWNER: WATER RESCURCES DEPT.	(10) LOCATION OF WELL:			
Name KROUSE RANCH, INC. SALEM. ORECON	County JACKSON Driller's well number			
Address 15877 N. APPLEGATE Rd.	Co of	R. 4	4)	W.M.
GRANTS PASS, ORE	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	THE LOT 00200			
New Well 🗗 Deepening 🛘 Reconditioning 🗀 Abandon 🗀				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	~?		#+
Rotary Driven Domestic Industrial Municipal	Static level 7 ft. below land st	urfoce	Data 7	27-7
Cable	Artesian pressure lbs. per square			· ~ ·
CLOTTO THOMAS TO	The same pressure ins. per square	; men.	Date	1(
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well b	elow cas	ing 6)
6 " Diam. from 0 ft. to 59 ft. Gage \$250	Depth drilled O ft. Depth of comple	ted wel	100	ft.
"Diam. from ft. to ft. Gage ft	Formation: Describe color, texture, grain size a	nd struc	ture of n	naterials;
Diani, ironi	and show thickness and nature of each stratur with at least one entry for each change of format	n and a ion Ren	quifer pe	netrated,
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal			
Type of perforator used	MATERIAL	From	то	swl
Size of perforations in. by in.	Blackcay	0	27	7
perforations from ft. to ft.				
perforations from ft. to ft.	BROW CLAY, FRACTURED	27_	53	
perforations from ft. to ft.	BASACT			
(7) SCREENS: Well screen installed? Yes No	DOOT LOOK ROSE			
Manufacturer's Name	PRACTURED BASACT	53_	100	
Type Model No.				
Diam. Slot size ft.				
Diam. Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is		, .		
lowered below static level /	- HOUIFER	62	85	185p
Was a pump test made? Yes No If yes, by whom? DRICLER				
Vield: 18 gal./min. with 50 ft. drawdown after hrs.				
" " "				
<i>II</i>				
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
nperature of water O Depth artesian flow encountered ft.	Work started 7 36 1977 Complete	d 7.	-27	1977
(9) CONSTRUCTION:	Date well drilling machine moved off of well		-27	1977
Well seal—Material used CEMENT	Drilling Machine Operator's Certification:			,
Well sealed from land surface to 00 ft.	This well was constructed under my	direct	super	vision.
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above a	are true	to my
Diameter of well bore below sealin.	[Signed] // CLS Molow]	Date	1-27	
Number of sacks of cement used in well seal 8/2 sacks	(Drilling Machine Operator)		1065	
How was cement grout placed? PUMPED	Drilling Machine Operator's License No.		1000	
	Water Well Contractor's Certification:			
The state of the s	This well was drilled under my jurisdi		nd this r	eport is
Was a drive shoe used? XYes □ No Plugs Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water? Yes No	Name FAYUW WELL VELLING (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address 1840 WILLOW LN		ρ .	
Method of sealing strata off	000	7		***********
·	[Signed] Units (Water Well Contra		******************	
Was well gravel packed? Yes No Size of gravel:		_ / _	,	
Gravel placed from ft. to ft.,	Contractor's License No. 6.22 Date	Jan		., 19