

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT RECEIVED STATE OF OREGON (Please type or print) MAY 25 1973 STATE ENGINEER SALEM OREGON

see // bb aa 385/44-10 G-8273 State Well No. State-Permit No.

Jack 17655

(1) OWNER:

Name Leon Lynch Address 520 Humburg Creek Rd, Applegate, Ore

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven [] Cable [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

CASING INSTALLED:

6" Diam. from 0 ft. to 30 ft. Gage 250 Threaded [] Welded [X]

PERFORATIONS:

Type of perforator used Size of perforations in. by in. Perforated? [] Yes [X] No

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [X] No If yes, by whom? 1: 35 gal./min. with 44 ft. drawdown after 1 hrs.

(9) CONSTRUCTION:

Well seal—Material used Cement Well sealed from land surface to 19 ft. Diameter of well bore to bottom of seal 9 in. Diameter of well bore below seal 6 in. Number of sacks of cement used in well seal 4 sacks

(10) LOCATION OF WELL:

County Jackson Driller's well number NE 1/4 NE 1/4 Section 10 T. 38s R. 4w W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 62 ft. Static level 22 ft. below land surface. Date 5-19-73 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6 ft. Depth drilled 86 ft. Depth of completed well 86 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: Brown clay of Albatross (0-12), Decomposed Serpentine (12-16), Hard Green Serpentine (16-62), Fractured Serpentine (62-65) with Water Bearing 25, Hard Green Serpentine (65-74), Fractured Serpentine (74-78) with Water Bearing 10, Hard Green Serpentine (78-86).

Work started 5-18 1973 Completed 5-19 1973 Date well drilling machine moved off of well 5-19 1973

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] George M. McCluskey Date 5-21, 1973 (Drilling Machine Operator) License No. 674

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Geo. M. McCluskey Well Drilling (Person, firm or corporation) (Type or print) Address 730 N.E. Clide Dr. Troutdale, Ore [Signed] George M. McCluskey (Water Well Contractor) Contractor's License No. 452 Date 5-21, 1973