NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

RECEIVED
JUN 23 1972
STATE ENGINEER
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

Jack 78015

State Well No. 39S/1W-3
State Permit No.

(1) OWNER:
Name Julian Battaile
Address 8909 Yank Gulch Rd.
Talent, Ore.

(2) TYPE OF WORK (check):
New Well XX Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary XX Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic XX Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded XX
6" Diam. from +1 ft. to 39 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes XX No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes XX No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes XX No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
jet test 3 gal./min. with 183 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used bentonite cement
Well sealed from land surface to 39 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 2 sacks
Number of sacks of bentonite used in well seal 4 sacks
Brand name of bentonite National
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes XX No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes XX No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes XX No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Jackson Driller's well number
¼ ¼ Section 3 T. 39S R. 1W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found ft.
Static level 23 ft. below land surface. Date 6/16/72
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 206 ft. Depth of completed well 206 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
top soil	0	5	
brown rock	5	13	
loose grey & brown rock	13	31	
grey rock	31	38	
hard grey rock	38	60	
grey & brown rock	60	105	
hard grey rock	105	146	
black & grey rock	146	190	
blue grey rock	190	206	

Work started 6/14/72 19 Completed 6/16/72 19
Date well drilling machine moved off of well 6/16/72 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Scott Hall (Drilling Machine Operator) Date 6/19/72 19
Drilling Machine Operator's License No. 750

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Rotary Drilling Co. (Person, firm or corporation) (Type or print)
Address 1044 W. 12th, Medford, Ore. 97501
[Signed] (Water Well Contractor)
Contractor's License No. 338 Date 6/19/72, 19

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119