

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED WATER WELL REPORT

NC

WATER RESOURCES DEPARTMENT

SALEM, OREGON 97310

within 30 days from the date of well completion.

OCT 13 1977

STATE OF OREGON

(Please type or print)

Jack
18170

State Well No. 395/2W-18

State Permit No. G-8681

WATER RESOURCES DEPT.

(Do not write above this line)

(1) OWNER:

SALEM, OREGON

Name Earl Brown

Address 10250 Sterling Crk. Rd.

Jacksonville, Ore.

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded

6 n. Diam. from 0 ft. to 40 ft. Gage 250

" Diam. from " ft. to " ft. Gage

" Diam. from " ft. to " ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.

perforations from " ft. to " ft.

perforations from " ft. to " ft.

perforations from " ft. to " ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from " ft. to " ft.

Diam. Slot size Set from " ft. to " ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?

Yield: gal./min. with " ft. drawdown after " hrs.

" " " " "

" AIR " " " "

Bailer test 20 gal./min. with 180 ft. drawdown after 1 1/2 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered " ft.

(9) CONSTRUCTION:

Well seal—Material used Cement

Well sealed from land surface to 38 ft.

Diameter of well bore to bottom of seal 10 in.

Diameter of well bore below seal 6 in.

Number of sacks of cement used in well seal 6 sacks

How was cement grout placed? poured

Was a drive shoe used? Yes No Plugs " Size: location " ft.

Did any strata contain unusable water? Yes No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? Yes No Size of gravel: "

Gravel placed from " ft. to " ft.

(10) LOCATION OF WELL:

County Jackson Driller's well number 1

1/4 1/4 Section 18 T. 39S R. 2W W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 90 ft.

Static level 60 ft. below land surface. Date 10/10/77

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 240 ft. Depth of completed well 240 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil--brown	0	8	
Shattered rock& clay-brown	8	26	
Basalt--gray	26	30	
" brown	30	32	
" black	32	90	
" gray	90	100	
" black	100	140	
" gray	140	145	
" black	145	194	
" gray	194	200	
" black	200	240	

Work started 10/10/77 19 Completed 10/10 19 77

Date well drilling machine moved off of well 10/10 19 77

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Liz Milkowski Date 10/12, 19 77

(Drilling Machine Operator)

Drilling Machine Operator's License No. 483

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Virgle Gribble Well Drilling

(Person, firm or corporation) (Type or print)

Address 8380 Ramsey Rd., Gold Hill, Ore.

[Signed] Wayne Milkowski

(Water Well Contractor)

Contractor's License No. 461 Date 10/12, 1977