NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORE ECEIVED

STATE OF OREGON

JAN20198 Well No. 405 8W-4bc

(Please type or print) (Do not write above this liggATER RESOURCES DEPT. No.

	SALEM ORFCON		
(1) OWNER:	(10) LOCATION OF WELL:		
Name U.S.F.S. Rogue River Nat'l Forest	County Jackson Driller's well number		
Address P.O. Box 520	SW 14 NW 14 Section 4 T. 40s R. 3w W.M.		
Medford, OR 97501	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well 🕮 Deepening 🗍 Reconditioning 🗍 Abandon 🗍			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	50	ft.
Rotary XX Driven   Domestic   Industrial   Municipal   Cable   Jetted	Static level 12 ft. below land s	urface. Date	1/7/78
Dug Bored Irrigation Test Well Other XX	Artesian pressure lbs. per squar	e inch. Date	•
CASING INSTALLED: Threaded ☐ Welded ☑x  6	(12) WELL LOG: Diameter of well to Depth drilled 100 ft. Depth of complete	_	6 100 ft.
" Diam. from	Formation: Describe color, texture, grain size and show thickness and nature of each stratu		
PERFORATIONS: Perforated?   Yes XX No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Sand, brown & Boulders	0 8	
perforations from ft. to ft.	Metavolcanic, grey fractured	8 12	
perforations from ft. to ft.	Metavolcanic, grey hard	12 35	+
perforations from ft. to ft.	Metavolcanic, grey hard W/slight fractures Non-		<u> </u>
(7) SCREENS: Well screen installed? ☐ Yes XK! No	water bearing	35 50	
Manufacturer's Name	Metavolcanic, grey hard		
Type Model No	W/ slight fractures, water		
Diam Slot size Set from ft. to ft.	bearing	50 80	
Diam. Slot size Set from ft. to ft.	Metavolcanic, grey hard W/		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	small amount of Quartz and	80 100	12
TOWELER DELOW STREET LEVEL	iron pyrite flakes	30 100	12
Was a pump test made? ☐ Yes ★No If yes, by whom?  Yield: gal./min. with ft. drawdown after hrs.			
" " " " " "			
" " "			
Air Begggytest 5 gal./min. with 80 ft. drawdown after 1 hrs.			
Artesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started 1/6 19 78 Complet		1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1/7	<sub>19</sub> 78
Well seal—Material used Cement Grout	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my Materials used and information reported best knowledge and belief	above are t	true to my
Diameter of well bore below seal	[Signed]		
Number of sacks of cement used in well seal sacks.  How was cement grout placed? Grout pump and drop pipe,	Drilling Machine Operator's License No. 1167		
	Water Well Contractor's Certification:		
	This well was drilled under my jurisd		is report is
Was a drive shoe used?XX Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.  Name McGlanahap Well Drilling		
Did any strata contain unusable water?   Yes XX No	(Person firm or comporation) (Type or print)		
Type of water? depth of strata	Address 141 NE Beacon Drive	Grants I	ass, OR
Method of sealing strata off	La ( 4Danle M/8	1/h	
Was well gravel packed? ☐ Yes XXNo Size of gravel:	[Signed] (Water Well Cond	ractor)	
Gravel placed from ft.		January	9 7
· · · · · · · · · · · · · · · · · · ·			