NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

Jack 18564

State Well No. 40s/3w-8cd

State Permit No.

(1) OWNER:
Name Don Fossen
Address 11771 Upper Applegate
Jacksonville, OR 97530

(2) TYPE OF WORK (check):
New Well XX Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary XX Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic XX Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded XX
6" Diam. from 0 ft. to 40 ft. Gage .250
4" Diam. from 0 ft. to 100 ft. Gage .250 plastic
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? XX Yes ☐ No.
Type of perforator used knife
Size of perforations 1/2 in. by 4 in.
82 perforations from 90 ft. to 100 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes XX No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes XX No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
XX Bailer Air test 5 1/2 gal./min. with 78 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement Grout
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 6 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal 6 sacks
How was cement grout placed?
Grout pump and drop pipe
Was a drive shoe used? XX Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes XX No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes XX No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Jackson Driller's well number 697
SE Se ¼ SW ¼ Section 8 T. 40 R. 3 W W.M.
Bearing and distance from section or subdivision corner
Tax Lot 1700
Permit 286-79w

(11) WATER LEVEL: Completed well.
Depth at which water was first found 38 ft.
Static level 17 ft. below land surface. Date 6/8/79
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 100 ft. Depth of completed well 100 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Clay, Brown, impervious	0	30	
Clay, brown and Boulders	30	38	
Rock, grey, fractured, water bearing	38	100	17

RECEIVED
JUN 1 1979
WATER RESOURCES DEPT
SALEM, OREGON

Work started 6/7/ 19 79 Completed 6/8 1979
Date well drilling machine moved off of well 6/8 19 79

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Guy Miller (Drilling Machine Operator) Date 6/13, 19 79
Drilling Machine Operator's License No. 1167

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name McClanahan Well Drilling (Person, firm or corporation) (Type or print)
Address 141 N.E. Beacon, Grants Pass, OR
[Signed] Ken McClanahan (Water Well Contractor)
Contractor's License No. 727 Date 6/13, 19 79

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119