NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report

are to be filed with the

WATER RESOURCES DEPARTMENT, AUG 2 71979 STATE OF OREGON SALEM, OREGON 97310 (Please type or print)

within 30 days from the date of well completion. (Please type or print)

State Permit No.

リング・ アンドン アンダウング		
(1) OWNER:	(10) LOCATION OF WELL:	
Name PROSPECT HOTEL	County JACKSON Driller's well number	
Address P.O. Box 215	5.10: 45.E.4 Section 29 T. 32 5 R. 3E. W.M.	
PROSPECT, ORE,	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	TAX LOT 2803	
New Well Deepening Reconditioning Abandon	7.77 7.07	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	_ a a em	
Rotary N. Driven	Depth at which water was first found 6	ft.
Cable		te 83-777- V
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Dat	te
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below easing	(0
Diam. from O ft. to AT ft. Gage 250	7	
"Diam. from 6 ft. to 190 ft. Gage 160 P.S.		
ft. Gageft.	Formation: Describe color, texture, grain size and structur and show thickness and nature of each stratum and aqui	e of materials; fer penetrated
PERFORATIONS: Perforated? Ves Cl No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
Tourstand, American	position of Static water Level and indicate principal water-	bearing strata.
Type of perforator used	MATERIAL From	To SWL
Size of perforations /83 in. by in.		2
33 perforations from 130 ft. to 190 ft.	Pumices Brown 2 1	•
perforations from ft. to ft.		<u>,0</u>
perforations from		
(7) SCREENS: Well screen installed? Yes X No	Lava - Gray 17 1 HT 8	
Manufacturer's Name	Lava-Corel Red BHG	
Type Model No.	Fava Star	92
Diam Slot size Set from ft. to ft.	Laya Stay Fea 10X 11	3
Diam Slot size Set from ft. to ft	Laya - Gray/ Pack 132	<u> </u>
(O) TIVET T PROCESS Decorate is consistent and a land	Lava - C-re/ 14411	51
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Lava- Gray / Perl 161 17	13
Was a pump test made? Yes No If yes, by whom?	Lava- Gray 175 18	37
Yield: gal./min. with ft. drawdown after hrs	Lava - Gray/Red 18719	3 166
" " "		
." " " " "		
gal./min. with Ait. drawdown after hrs		
Artesian flow g.p.m. — perature of water Depth artesian flow encountered ft	0 01 50	
perature of water Depth artesian flow encountered ft	Work started 8 - 2 197 Completed 8 -	ZZ 19 69
(9) CONSTRUCTION:	Date well drilling machine moved off of well	19 70
Well seal-Material used torthing Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct su	ıpervision.
Diameter of well bore to bottom of seal in.	Materials used and information reported above are best knowledge and belief	true to my
Diameter of well bore below seal	[Signed Date O	72 1979
Number of sacks of cement used in well sealsacks	(Drining Machine Operator)	
How was cement grout placed?	Drilling Machine Operator's License No	L
1 remie Dipe	Water Well Contractor's Certification:	
	r 🛊	inia mamant 1-
Was a dained as a second of the second of th	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? ▼ Yes □ No Pings Size: location ft.	Name MARTINSON WELL DRILLING INC.	
Did any strata contain unusable water? Tes No	(Person, firm or corporation) (Type	or print)
Type of water? depth of strata	Address & I DALL & D. EAGLE POINT, ORE	
Method of sealing strata off	[Signed] Moulins	
Was well gravel packed? ☐ Yes No Size of gravel:	(Water Well Contractor)	
Gravel placed from ft_to ft.	Contractor's License No. 67 Date 8 - 23	1929