"NOTICE TO WATER WELL CONTRACTOR

WATER RESOURCES DEPT.	e this line)	State Fermit No.
within 30 days from the date NIV 2 (19/8)	print)	State Permit No.
WATER RESOURCES DEPARTMENT STATE OF O	REGON 2138	State Well No. 3 & 5/36-20
The original and first copy of this report are to be filed with the CELL WATER RESOURCES DEPARTMENT STATE OF OF SALEM, OREGON 97310 (Please type of	REPORT ACT	20/2-2

(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:			
Name Louis Biden	County Jackson Driller's well number			
Address 74 Mill Creek Drive,	SE 14 SW 14 Section 29 T. 32S R. 3E W.M.			
Prospect, Or.	Bearing and distance from section or subdivision co			
(2) TYPE OF WORK (check): New Well Deepening Reconditioning Abandon Deepening Abandon Deepening Reconditioning Deepening Deep	Tax lot1500 Permit663-78W			
If abandonment, describe material and procedure in Item 12.	- (11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 260	ft.		
Rotary M Driven Domestic M Industrial Municipal Domestic M Industrial Municipal Domestic M Industrial D In				
Dug □ Bored □ Irrigation □ Test Well □ Other □	- I			
CASING INSTALLED: Threaded [Welded T	por square inc	n. Date		
——6	(12) WELL LOG: Diameter of well below	casing 6		
" Diam. fromft. toft. Gage	Depth drilled 380 ft. Depth of completed	well 380 ft.		
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and s	tructure of materials:		
	with at least one entry for each change of formation	d aquifer penetrated,		
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal	water-bearing strata.		
Type of perforator used	MATERIAL Fro	om To SWL		
Size of perforations in. by in.	Pumicebrown	0 10		
perforations fromft. toft.	Tarro mari	10 80		
perforations fromft. toft.		80 90		
perforations from ft. to ft.	** GRAY	90 110		
(7) SCREENS: Well screen installed? Yes No	brown 1	10 116		
Manufacturer's Name	- gray 1:	16 150		
TypeModel No.	Drown 1	50 162		
Diam Slot size Set from ft. to ft.	11	52 180		
Diam. Slot size Set from ft. to ft.	11	30 190 -		
(8) WELL TESTS: Drawdown is amount water level is	11 1	1 1 1 1 1		
lowered below static level	gray 21			
Was a pump test made? 🗌 Yes 💆 No If yes, by whom?		50 380		
Yield: gal./min. with ft. drawdown after hrs.	300' of 5' metal liner installed-	-last 60'		
n n	slotted			
ATR "				
Bailer test 10 gal./min. with 240 ft. drawdown after $1\frac{1}{2}$ hrs.				
Artesian flow g.p,m.				
perature of water Depth artesian flow encounteredft.	Work started 11/20 19 78 Completed 11	/00		
(9) CONSTRUCTION:		100		
Ø = = = = 1		/22 19 78		
And the state of t	Drilling Machine Operator's Certification:			
Diameter - 10	This well was constructed under my direct supervision. Materials used and information reported above are true to my			
Diameter of well bore to bottom of seal in. Diameter of well bore below seal in.	best knowledge and belief.			
Number of sacks of cement used in well seal 9 sacks	[Signed] Date 11/24 , 19.78			
How was cement grout placed? poured		83		
and the state of t				
	Water Well Contractor's Certification:			
And the state of t	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this report is		
Was a drive shoe used? X Yes No Plus Size: location ft.	Name Virgle Gribble Well Drilling			
Oid any strata contain unusable water? Yes X No	(Person, firm or corporation)			
Type of water? depth of strata	Address 8380 Ramsey Rd., Gold Hill,	Ore.		
Method of sealing strata off	[Signed] Lyn Milkowsh			
Was well gravel packed? [] Yes X No Size of gravel:	(Water Well Contractor)			
Gravel placed from ft. to ft.	Contractor's License No. 705 Date 11/24	ł 19 ⁷⁸		
4== ==		± U		