NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

filed with the

WATER WELL REPORT 3 1973

The state of oregon AUG 2 3 1973

State Well N	्र 10. देख	 13	( -	29
		 G		

STATE ENGINEER, SALEM, OREGON 973104 within 30 days from the date of well completion.

(Please type or printSTATE ENGINEER

(Do not write above this IMALEM, OREGON State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	
Name Louis Biden	County Jackson Driller's well nu	ımber
Address 74 Mill Creek Drive	14 14 Section 29 T. 32S	R. 3E W.M.
Prospect, oregon	Bearing and distance from section or subdivision	•
(2) TYPE OF WORK (check):	Bedring and distance from Section of Subdivision	JAI COINCI
New Well 🖫 Deepening 🗌 Reconditioning 🗍 Abandon 🗎		
If abandonment, describe material and procedure in Item 12.	(44) YUARRED YERRES	***
	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 118	}ft.
Rotary $lacksymbol{\Delta}$ Driven $\Box$ Domestic $\Box$ Industrial $\Box$ Municipal $\Box$	Static level 80 ft. below land s	urface. Date /14/73
Dug 🗌 Bored 🗎   Irrigation 🖂 Test Well 🖂 Other 🔼	Artesian pressure lbs. per squar	e inch. Date
CASING INSTALLED: Threaded   Welded   Welded   Trailer   Cou	rt	
(5) CASING INSTALLED: Threaded Welded	(19) WELL LOC.	elow casing6
6 " Diam. from0 ft. to65ft. Gage250	Depth drilled 224 ft. Depth of comple	eted well 224 ft.
" Diam. from	Formation: Describe color, texture, grain size a	
"Diam. from ft. to ft. Gage	and show thickness and nature of each stratum	n and aquifer penetrated,
PERFORATIONS: Perforated? Yes KNo.	with at least one entry for each change of format position of Static Water Level and indicate princ	
Type of perforator used		
	MATERIAL	From To SWL
Size of perforations in. by in.	Pumice & boulders-brown	0 5
perforations from ft. to ft.	Lava Oblack-hard	5 26
perforations from ft. to ft.	81CA	26 30
perforations from ft. to ft.	black-hard	30 43
(7) SCREENS: Well screen installed?   Ves 5-No	gray	43 46
	black-hard	46 118
Manufacturer's Name	red	118 132
Type Model No.	black-hard	132 166
Diam. Slot size Set from ft. to ft.	red red	166 181
Diam. Slot size Set from ft. to ft.	gray	181 194
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	black-hard	194 224
	200 foot of 5 1 1 7	
Was a pump test made?  Yes No If yes, by whom?	220 feet of 5 inch line	c installed
d: gal./min. with ft. drawdown after hrs.	perforated from 160 to	220
" "	75 perforations ½ inch	oy 17 inches
" ATR " "		
Bailer test 45 gal./min. with L44t. drawdown after 13hrs.		
<u> </u>	0/77	
iperature of water Depth artesian flow encountered ft.	Work started 8/13 1973 Complete	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3/14 1973
Well seal—Material used Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface to60ft	This well was constructed under my	direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above are true to my
Diameter of well bore below seal	[Signed] in Mulkowel 1	Date8./20, 197.3
Number of sacks of cement used in well seal	[Signed] (Drilling Machine Operator)	
Number of sacks of bentonite used in well seal	Drilling Machine Operator's License No	483
Brand name of bentonite		
Number of pounds of bentonite per 10 gallons	Water Well Contractor's Certification:	
of water lbs./100 gals.	This well was drilled under my jurisdic	tion and this report is
was a drive shoe used? ☐ Yes ☐ Xo Plugs Size: location ft.	true to the best of my knowledge and believe	ef.
Did any strata contain unusable water?  Yes No	Name Virgle Gribble Well I (Person, firm or corporation)	rilling
Type of water? depth of strata	1	
	o o namsey ka	old Hill, Ore.
Method of sealing strata off	[Signed] Wayne ///llPou	vaki
Was well gravel packed? Yes No Size of gravel:	Water Well Contra	
Gravel placed from ft. to ft.	Contractor's License No. 461 Date	8/20 , 1973
(USE ADDITIONAL SE	EETS IF NECESSARY)	SD*45656-110