NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report · are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

W WATER WELL REPERCE EIVED

State Well No. 345

STATE OF OREGON JUN 191979 State Well No. 345/3W (Please type or print)

(Do not write above this line)

(Do not write above this line) SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name David Gilliver	County Jackson Driller's well number 4/6/
Address 13701 E. Evans Cn. Rd	14 1/4 Section 32 T. 345 R. 3 W W.M
Rogue Kiven Onegon	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	T. L. 710
New Well ▼ Deepening □ Reconditioning □ Abandon □	- Penmit # 746- 78W
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found /2/ ft
Rotary Driven Domestic Industrial Municipal	Static level 79 ft. below land surface. Date 5-32-75
Dug ☐ Bored ☐ Irrigation ▼ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 6
6 "Diam from 0 ft to 60 ft Gage 250	Depth drilled 235 ft. Depth of completed well 235 ft.
	Formation: Describe color, texture, grain size and structure of materials
Diant, from	and show thickness and nature of each stratum and aquifer penetrated with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Soil 01
ft. to ft.	Yellow Clay 1 24
perforations from ft. to ft.	Decomposed Busalt 24 53
perforations from ft. to ft.	Gray Baselt 53 121
(7) SCREENS: Well screen installed? Yes No	- Gray Basa 1 + Frantine 121 122 79
Manufacturer's Name	Gray Busult 122 229
Type Model No.	Gruy Busalt Fraction 229 233 79 Gruy Busolt 233 235
Diam Slot size Set from ft. to ft.	0 130 30 11 233 233
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is	
Was a pump test made? Tyes \(\subseteq \) No If yes, by whom? On Iller	
774-14. 77	
gai./min. with / 10 ft. drawdown after / hrs.	
" " " "	4
Pollon test	
Artesian flow g.p.m. ft. drawdown after hrs.	
mperature of water 56 Depth artesian flow encountered	
	Work started 5-2/ 1979 Completed 5-22 1979 Date well drilling machine moved off of well 5-22 1979
(9) CONSTRUCTION: Well seal—Material used	
	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface toft. Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my
Diameter of well bore below sealin.	best knowledge and belief. [Signed] U
Number of sacks of cement used in well seal / c sacks	[Signed] U. Bushingh Date 5-37, 1979
How was cement grout placed? Grout Pump	Drilling Machine Operator's License No. 788
	Water Well Contractor's Contractor
	Water Well Contractor's Certification:
Tire and the second sec	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name 66. 9. Bunlington Onilling
Did any strata contain unusable water	(Person, firm or corporation) (Type of print) Address SOX 928 Malin Che
Type of water? depth of strata	Address J. C 564 728 Malin One
Method of sealing strata off	[Signed] Burling T
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ftfo ft.	Contractor's License No. 232 Date 3-27 1979