NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report

SALEM, OREGON 97310 within 30 days from the date

of well completion.

The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTITION OF THE OF OREGON SALEM. OREGON 97210

State Well No. 345/3W-32dc

State Permit No. 6-855Z

(Please type or print) SEP 1 6 1977 (Do not write above this line) WATER RESOURCES DEPT.

(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:	
Name Greenlaw, Charles	County Jackson Driller's well number	
Address 3777 E Fuans Ch. Rd.	¼ Section 32 T. 34	
Rogue River, Ore	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	- (11) WATER LEVEL: Completed w	rell
(3) TYPE OF WELL: (4) PROPOSED USE (check):		12/
Rotary Driven Domestic Municipal	- 3	
Davie G Setted G		
Total I Total	Artesian pressure lbs. per squar	e inch. Date
CASING INSTALLED: Threaded □ Welded	(12) WELL LOG: Diameter of well to	6
" Diam. from 1 ft. to 5 / ft. Gage 225	2	
ft. Gage ft. Gage		
ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
PERFORATIONS: Perforated? Ves No		
1 circulated: [] 1 cs 4 110.	position of static water Level and indicate prin	cipal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	- 501/- 610WH	02
perforations from ft. to	a. Clay-chouse	2 6
perforations from ft. to ft.	t. Sandstene-blown	6 12
perforations from ft. to f	i. Clay - Evour	12 49
(7) SCREENS: Well screen installed? Yes Wo	Clay with Gosalt	49 57
200 210	645a/f-6/40	57 96
Manufacturer's Name		96 112
TypeModel No.	PERCENCE COLLAR CONTRACTOR	112 136
Diam. Slot size Set from ft. to f	CALSAIT ENVINOUN	136 141 38
Diam. Slot size Set from ft. to ft. to	Easaft -6/40	141 145
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes ☑ No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hr	s.	
" "		
" "		
Salier test /00 gal./min. with/03 ft. drawdown after / hr.	s,	
Artesian flow g.p.m.		
remperature of water Depth artesian flow encountered f	77	
		ed 9 -/3 1977
CONSTRUCTION:	Date well drilling machine moved off of well	<u> ゲーノ3 19ファ</u>
Well seal-Material used Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct supervision.	
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.	
Diameter of well bore below seal in.	[Signed] Granks Gulfreat Date 9-14 1977	
Number of sacks of cement used in well sealsack	(Drilling Machine Operator)	
How was cement grout placed?	Drilling Machine Operator's License No	317
From Ecttoria Up	TYPE AND THE COLUMN ASSESSMENT AS	
The second secon	Water Well Contractor's Certification:	
The state of the s	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? 🗌 Yes 💽 Wo Plugs Size: location ft	Name Charles Application of the control of the cont	
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address 1923 Dolla Wall	15 Rd Mod
Method of sealing strata off		LL_
Was well gravel packed? [] Yes [No. Size of gravel:	[Signed] (Water Well Contra	(hvood
Gravel placed fromft. to	Contractor's License No. 5 15 Date	9-111
11. 10	Date	· / 7 19//