NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

## STATE OF OREGON

(Please type or print)

(Do not write above this line)

Jack			,	21.5	1,=	6ca
Or a stor	State	Well No	o <del>s</del>	<i>ر حو</i> د	VF-	weck
197	State	Permit	No.			anadillidagi'a as _a

(1) OWNER:	(10) LOCATION OF WELL:				
Name GORDON STANLEY	County JACKSO N Driller's well number				
Address /// 85 /404 /40					
FAGLE COINT DRE	N.E. 14 S.W. 14 Section 6 T.36 S.R. /E. W.M.				
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner				
New Well Deepening Reconditioning Abandon	TAX LOT 1700				
If abandonment, describe material and procedure in Item 12.	PERMIT 308-79-W.				
	(11) WATER LEVEL: Completed well.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 68 ft.				
Rotary Driven Domestic Maintenant Municipal Domestic Municipal Domestic	Static level 52 ft. below land surface. Date 6-19-7				
Dug	Artesian pressure lbs. per square inch. Date				
CASING INSTALLED:  Threaded   Welded	(12) WELL LOG: Diameter of well below casing  Depth drilled 2.5 ft. Depth of completed well 2.5 ft.  Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.				
Type of perforator used	MATERIAL, From To SWL				
Size of perforations in. by in.	SOIL BROWN 0 2				
perforations fromft. toft.	CLAY BROWN 28				
perforations fromft. toft.	CLAGSTONE BROWN 80 20				
perforations from ft. to ft.	SANDSTONE BROWN 20 28				
(7) SCREENS: Well screen installed?   Yes No	BANDSTONE BLUE 28 68				
	CLAUSTONE, RED 188 191				
Menufacturer's Name	SANDSTONE SPREY 191 208				
Diam	BASALT MREY 208225 52				
Diam. Slot size Set from ft. to ft.	30.73				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level  Was a pump test made?  Yes No If yes, by whom?					
Yield: gal./min. with ft. drawdown after hrs.	JUN 2 6 1979				
" " " " "					
11 11 N	WATER RESOURCES DEPT				
Baller test / 5 gal./min. with / 73 ft. drawdown after 2 hrs.	SALEM, OREGON				
nperature of water Depth artesian flow encounteredft.	Work started 6-18-19 Gompleted 6-19-1979				
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6-19- 1979				
Well seal-Material used PORTLAND CEMENT	Drilling Machine Operator's Certification:				
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my				
Diameter of well bore to bottom of seal in.	best knowledge and belief.				
Diameter of well bore below sealin.	[Signed] Joseph MedinaDate 6-20 1979				
Number of sacks of cement used in well sail sacks  How was cement grout placed? PRF: SSURE	Drilling Machine Operator's License No.				
How was cement grout placed? PRI PIPE	Water Well Contractor's Certification:				
	and the same of th				
Wing a drive about model of the first three Committee of the committee of	This well was drilled under my jurisdiction and this report is true-to the best of my knowledge and belief.				
Was a drive shoe used?   Yes No fue Size: location ft.	Name MARTINSON WELL DRILLING INC.				
Did any strata contain unusable water Yes No  Type of water? depth of strata	Address 8 BALL RD. EAGLE POWT, ORB				
Method of sealing strata off	P. III +				
	[Signed] Conald & Marlings				
THE TOTAL STATE OF THE STATE OF	(Water Well Contractor)				
Gravel placed from tt. (USE ADDITIONAL SH	Contractor's License No. 067 Date 6-2 20 , 1979				