## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

## WATER WELL REPRECEIVED

()	FOREGON MAY 1 1975 State Well No.	365/1=-18 b
STATE ENGINEER, SALEM, OREGON 97310 (Please type within 30 days from the date of well completion. (Do not write a	pe or print)  above this life ATE ENGINEERState Permit N	- ·
	SALEM, OREGON	
(1) OWNER:	(10) LOCATION OF WELL:	
Name DEANE OWENS	County JACKS CW Driller's well no	umber
Address 1938 HERDIAN RD	1. 365	
EAGLE POINT ORE	Bearing and distance from section or subdivisi	,
(2) TYPE OF WORK (check):	APPRO. 1500' E. AND 900'S. FROM	
New Well	N.W. CORNER,	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	1-5
Rotary Driven D Domestic W Industrial D Manufacture		f. 1
Cable	4.1	surface, Date 4-28-75
CACTAIC MACHAELET	Artesian pressure lbs. per squar	e inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 6"	
"Diam fromft toft Gage	Depth drilled \$2 ft. Depth of completed well \$2 ft.	
"Diam. from ft. to ft. Gage ft	Formation: Describe color, texture, grain size a	and structure of materials:
Tt. toTt. Gage	and show thickness and nature of each stratum	n and aquifer penetrated.
PERFORATIONS: Perforated?   Yes 2 No.	with at least one entry for each change of format position of Static Water Level and indicate princ	tion. Report each change in cipal water-bearing strata.
Type of perforator used	B.C. A. TUTPUT A.Y.	
Size of perforations in, by in.		From To SWL
perforations fromft. toft.		0 1
		0 00 10
perforations fromft. toft.	CLAYSTONE, BLUE	8 82 12
perforations from ft. to ft.	***	
(7) SCREENS: Well screen installed?   Yes  No		
Manufacturer's Name		
Type Model No.	The state of the s	-
Diam Slot size Set from ft. toft.		
Diam. Slot size Set from ft. to ft.		
8) WELL TESTS:  Drawdown is amount water level is lowered below static level		
Was a pump test made?  Yes No If yes, by whom?		1
rield: gal./min. with ft. drawdown after hrs.		
" " " "		
" " "	3- 3- 47. — 1-1 - 4- 21	
gal./min. with 70 tt. drawdown after hrs.		
	1 12 15 17 17 17 17 17 17 17 17 17 17 17 17 17	
Artesian flow g.p.m.	The control of the Co	
perature of water Depth artesian flow encounteredft_	Work started 4-28 19 25 Completed	1 4-28 1975
9) CONSTRUCTION:	Date well drilling machine moved off of well	4-28 1975
Vell seal-Material used PRESSURE Cement Geout	Drilling Machine Operator's Certification:	7.0
	This well was constructed under my	direct cure product
Well sealed from land surface toft.	Materials used and information reported a best knowledge and belief.	above are true to my
Diameter of well bore to bottom of seal		
Number of sacks of cement used in well seal sacks	[Signed] Market Date 4-38, 1975	
Number of sacks of bentonite used in well setsacks	Drilling Machine Operator's License No	622
Brand name of bentonite		* ·
Yumber of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used?  Yes No Plus Size: location ft.	and to the best of my knowledge and belief,	
Did any strata contain unusable water [] Yes No	Name MARTIN SON WELL DRILLING	
Type of water? deth of strata	Address 81 BALL Rd. EAGL	(Type or print)
Method of sealing strata off	Care Marie M	E FOINT, ORE.
	[Signed] J. W. Marlinson	:N
	(Water Well Contrac	etor)
Gravel placed fromft_toft.	Contractor's License No. HO 6. Date	4-28 19 75