NOTICE TO WATER WELL CONTRACTOR The original and first copy The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT:

STATE OF OREGON

(Please type or print)

(Do not write above this line)

WATER WELL REPORT:

State Well No. 395/1E-/3

(Please type or print)

(Do not write above this line)

within 30 days from the date of well completion.

(Do not write above this line)

WATER RESOURCES DEPT.

(1) OWNER:	(10) LOCATION OF WELL			
Name Delhert Jabiarnon	County ACKSON Driller's well number			
Address 30 H.5 Newby lab	14 14 Section 13 T. 15 W.M.			
Garland, Anga	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	NW4 of S. E. of N.W. S. 13 T. 39s. R. I.E.			
New Well Deepening Reconditioning Abandon	47 47 47 47			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 9 / ft.			
Rotary Driven Domestic Mindustrial Municipal	Static level () ft. below land surface. Date $4-30$			
Cable Jetted Solution Test Well Other	Artesian pressure / 2 lbs. per square inch. Date 4 - 30-			
(5) CASING INSTALLED: Threaded Welded A "Diam. from	(12) WELL LOG: Diameter of well below casing Depth drilled / / Off. Depth of completed well / (A) ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in			
F PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	,	<u>1</u>	
Type of perforator used	MATERIAL	From	То	swl
Size of perforations in. by in.	Sal	0	2	*****
perforations from ft. to ft.	Elong	2	20	•
perforations fromft. toft.	Elan (with publica)	20	27	
perforations fromft. toft.	gesy arras pravoct	22	2-/	
(7) SCREENS: Well screen installed? Yes No Manufacturer's Name	Shale noch (hand)	2.7	62	£
Type Model No.	Baselt	42	67	
Diam Slot size Set from ft. to ft.	Sholy lock (hard)	67	91	
Diam Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Banult	71	140	0
Was a pump test made? Yes No If yes, by whom?				
i: gal./min. with ft. drawdown after hrs.				
, , , , , , , , , , , , , , , , , , ,		1		
" " " "		 		
Bailer test gal./min. with ft. drawdown after hrs.		\vdash		
sian flow /, 5 D g.p.m.				
temperature of water 17 Depth artesian flow encountered 4/ ft.	Work started 4 - 2 7 19 76 Completed 4 - 2 9 19 76			
9) CONSTRUCTION:	Date well drilling machine moved off of well $3-3$ 1976			
n - 3-4	Drilling Machine Operator's Certification:			
Well seal—Material used	This well was constructed under my direct supervision.			
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.			
Diameter of well bore below sealin.	[Signed] 6, 9, Studebahe Date 5-3, 1976			
Number of sacks of cement used in well seal				
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No			
Brand name of bentonite	Water Well Contractor's Certification:			
Tumber of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is			
f water	true to the best of my knowledge and belief.			
Vas a drive shoe used? Yes No Plugs	Name Of gratudetatu			
Did any strata contain unusable water?	Address 55 W. Newada St. (I) bland			
type of water? $9/4$ depth of strata $9/-140$	Address 30 Milliand			
Method of sealing strata off	[Signed] City Stiede bahr			
Was well gravel packed? [] Yes 1 No Size of gravel:	(Water Well Contractor)			
Gravel placed from ft. to ft	Contractor's License No. & O Date 5-37, 19/6,			