NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

Jack 2147

State Well No. 41S/2E-18bd

State Permit No.

(1) OWNER:
Name Gail Willard
Address 55 Beach Hill Gold

(2) TYPE OF WORK (check):
New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary [X] Driven []
Cable [] Jetted []
[redacted] [] Bored []

(4) PROPOSED USE (check):
Domestic [X] Industrial [] Municipal []
Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:
Threaded [] Welded [X]
6 " Diam. from 0 ft. to 20 ft. Gage .250
" Diam. from ft. to ft. Gage
[redacted]" Diam. from ft. to ft. Gage

(6) PERFORATIONS:
Perforated? [] Yes [X] No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? [] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
[redacted]s a pump test made? [] Yes [X] No If yes, by whom?
[redacted]ield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
[redacted]Bailer test 150 gal./min. with 20 ft. drawdown after 1 hrs.
[redacted]esian flow g.p.m.
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 6 sacks
How was cement grout placed? Pumped Down Hole Space
Was a drive shoe used? [X] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Jackson Driller's well number 58-79
SW ¼ NW ¼ Section 18 T. 41S R. 2E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 103 ft.
Static level 11 ft. below land surface. Date 10-15-79
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 135 ft. Depth of completed well 135 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil	0	10	
Sandstone	10	135	11

RECEIVED
OCT 29 1979
WATER RESOURCES DEPT
SALEM, OREGON

Work started 10-15 19 79 Completed 10-15 19 79
Date well drilling machine moved off of well 10-15 19 79

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Art Cart (Drilling Machine Operator) Date 10-19, 19 79
Drilling Machine Operator's License No. 997

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Art Cantar Well Drilling (Person, firm or corporation) (Type or print)
Address 244 Johnson Rd Sutter Cr
[Signed] Art Cart (Water Well Contractor)
Contractor's License No. 599 Date 10-19, 19 79

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119