

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED

APR 2 1973

STATE ENGINEER
SALEM OREGON

State Well No.

335/W-36^a

State Permit No.

(1) OWNER:

Name William Steadman
Address STAR RT. 1 Box 648
TRAIL, ORE 97541

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
6" Diam. from 0 ft. to 22 ft. Gage 150
" Diam. from " ft. to " ft. Gage
" Diam. from " ft. to " ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level.

Was a pump test made? Yes No If yes, by whom?
AIR RETURN
Pump test 60 gal./min. with 58 ft. drawdown after 1 hrs.

Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Pressure Cement Grout
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal 9 3/8 in.
Diameter of well bore below seal 6 in. 8
Number of sacks of cement used in well seal 8 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County JACKSON Driller's well number
1/4 NE 1/4 Section 36 T. 33S. R. 1W W.M.

Bearing and distance from section or subdivision corner
APPRO. 500' W. AND 800' S. FROM
N.E. CORNER.

(11) WATER LEVEL: Completed well.

Depth at which water was first found 32 ft.
Static level 25 ft. below land surface. Date 3-27-73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"
Depth drilled 83 ft. Depth of completed well 83 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
SOIL, BLACK	0	3	
CLAYSTONE, BROWN	3	13	
BOULDERS, Small, BROWN	13	16	
CLAYSTONE, BLUE	16	83	25

Work started 3-27 1973 Completed 3-27 1973
Date well drilling machine moved off of well 3-27 1973

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Ronald Martinson Date 3-27, 1973
(Drilling Machine Operator)
Drilling Machine Operator's License No. 622

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name MARTINSON WELL DRILLING
(Person, firm or corporation) (Type or print)
Address 81 BALL RD. EAGLE POINT, ORE.
[Signed] J. W. Martinson
(Water Well Contractor)
Contractor's License No. 406 Date 3-27, 1973