NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF GONGON
(Please type or print)

V'ATE (bo not write above this line).

State Well No. 35 5 / 1 w - 17 State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:		
Name Jackson County Fire District #3	County Jackson Driller's well number		
Address8333 Agate Rd.	34 34 Section 17 T. 35S	R. 1W	W.M.
White City, Ore.	Bearing and distance from section or subdivision		
(2) TYPE OF WORK (check):	NEL OF 3 WK		
New Well Deepening □ Reconditioning □ Abandon □	79 8 7		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 46		ft.
Rotary Driven Domestic Dindustrial Municipal	Static level 60 ft. below land surface. Date 8/1/78		
Cable Jetted		•	4.0
Dug	Artesian pressure lbs. per square	e inch. Date	
CASING INSTALLED: Threaded Welded X	(12) WELL LOG: Diameter of well b	elow cosing (5
6 " Diam. from 0 ft. to 42 ft. Gage 250	Depth drilled 280 ft. Depth of comple	-00	ft.
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size a		matarials
" Diam. fromft. toft. Gage	and show thickness and nature of each stratus		
THE PLOP & THOUGH	with at least one entry for each change of format position of Static Water Level and indicate prin		
PERFORATIONS: Perforated? Yes No.			· · · · · · · · · · · · · · · · · · ·
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Soilbrown	0 2	
perforations from ft. to ft.	Bouldersmedbrown & gray	2 12	
perforations from ft. to ft.	Claystonebrown	12 32	
perforations fromft. toft.	Chnglomerategray	<u>32 118</u>	
(7) SCREENS: Well screen installed? ☐ Yes ▼ No	-Claystone9-black	118 130	
in the second	-Claystonegray	130 140	
Manufacturer's Name Type Model No	Basaltgray	140 170	ļ
Diam. Slot size Set from ft. to ft.	-Glaystonepink	170 183	
Diam. Slot size Set from ft. to ft.	Claystonegray	<u> 183 280</u>	
District Annual Control of the Contr			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes K No If yes, by whom?			
St. January St.			
Yield: gal./min. with ft. drawdown after hrs.	4.		
The second secon			
AIR AT 200	(a		
Bailer test 15 gal./min. with 20 ft. drawdown after 1½ hrs.	the state of the s		
Artesian flow g.p.m.	• • • • • • • • • • • • • • • • • • •		L
perature of water Depth artesian flow encountered ft.	Work started 8/1 1978 Complete	ed 8/1	1978
(A) CONCEDICATION.	Date well drilling machine moved off of well	8/1	1978
(9) CONSTRUCTION: Cement	Drilling Machine Operator's Certification:		
Well seal—Material used	This well was constructed under my	direct super	vision.
Well sealed from land surface toft.	Materials used and information reported	above-are true	e to my
Diameter of well here below seal	best knowledge and belief.	Date 8/3	78
Diameter of well bore below seal in. Number of sacks of cement used in well seal seaks.	[Signed] (Drilling Machine Operator)	_	, 19
How was cement grout placed? pressure pumped	Drilling Machine Operator's License No. 483		
How was centent group placed			
	Water Well Contractor's Certification:	,	
	This well was drilled under my jurisdi true to the best of my knowledge and bel	ction and this r	eport is:
Was a drive shoe used? X Yes \(\) No Plus Size: location ft.	Name Virgle Gribble Well Drilli		
Did any strata contain unusable water? Yes 🕱 No	(Person, firm or corporation)	(Type or pri	nt)
Type of water? deptof strata	Address 8380 Ramsey Rd., Gold Hi	1.1Ore	
The second secon	1- mill	<i>A</i>	
Method of sealing strata off Was well gravel packed? TVes TVo: Size of gravel:	[Signed] (Water Well Contr.	4-*actor)	
was well graver packed.	- 12.3 (4) (4) (4) (4) (4) (4) (4) (4) (4) (4)	73	.78
Gravel placed from	Contractor's Interise No.		, 19
(USE ADDITIONAL SE	(EETS IF NECESSARY)	g	P*45656-119