NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

JACK WATER WELL REPORT EIVE D

293 STATE OF OREGON JUL 271973 State Well No. 3

(Please type or STATE ENGINEER

(Do not write above this GALEM OREGON TE Permit No.

	J, C, Pe	rmit #557-73W	
(1) OWNER:	(10) LOCATION OF WELL:		
Name Shady Vista Mobile Park	County Jackson Driller's well number		
Address P.O. Box 94			
Shady Cove, Oregon		-	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner		
New WellXX Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.			
	- (11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 94 ft.		
Rotary XX Driven	Static level 85 ft. below land st	urface. Date 7-12-7	
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square	inch. Date	
(5) CASING INSTALLED: Threaded Welded XX	(12) WELL LOG: Diameter of well below casing		
6 "Diam. from +1 ft. to 33 ft. Gage •250	Depth drilled 1000ft. Depth of completed well		
ft. toft. Gage			
" Diam. from	Formation: Describe color, texture, grain size at and show thickness and nature of each stratum		
PERFORATIONS: Perforated?   Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	rock gravel & brown clay	0 3	
	brown claystone	3 28	
perforations from ft. to ft.	blue claystone	28 92	
perforations from	blue gray claystone	92 130	
perforations fromft. toft.		130 200	
(7) SCREENS: Well screen installed?   Yes X No	Bray pagerro	10 200	
Manufacturer's Name	A Company of the second		
Type Model No.			
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS. Drawdown is amount water level is	<u>*</u>		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level DESERT	PUMP		
Was a pump test made? A Yes No If yes, by whom?			
Yal: 30 gal./min. with 45 ft. drawdown after 2 hrs.			
Sign continous yield " 10 "			
n en			
XEANOX testet 45 gal./min. with 45 ft. drawdown after 1 hrs.			
	The second secon		
Astesian flow g.p.m.	7 30 RO		
Depth artesian flow encounteredft.		17-13-73 19	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7-13-73 19	
Well seal—Material used Cement	Drilling Machine Operator's Certification:	and the second second	
Well sealed from land surface to	This well was constructed under my Materials used and information peported a bott bott bott bott better the work of the bott bott better the work of the the w	direct supervision.	
Diameter of well bore to bottom of seal in.	best knowledge and belief.		
Diameter of well bore below seal in.	[Signed] Date 7-20-739		
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 750		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is		
of water	I true to the best of my knowledge and helief		
Was a drive shoe used? ☐ Yes X No Plus Size: location ft.  Did any strata contain unusable water? ☐ Yes X No	Name Rotary Drilling Co.  (Person, firm or corporation) (Type or print)		
	(Person, firm or corporation) (Type or print)  Address 1207 Sage Rd. Medford, Ore, 97501		
Type of water? depth of strata		14, 016, 9/501	
Method of sealing strata off	[Signed] U.V. Hawled		
Was well gravel packed? ☐ Yes 🐧 No Size of gravel:	(Water Well Contrac	7 7	
Gravel placed from ft. to ft.	Contractor's License No. 332 Date	7-20-73 , 19	