NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
SEP 14 1970
STATE ENGINEER
SALEM, OREGON

JACK 3274

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 35/2W-4 6a

State Permit No. G 5787

(1) OWNER:
Name Dunn, Larry
Address 14995 Meadows Rd. Central Pt. Ore.

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☑ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:
Threaded ☐ Welded ☑
6" Diam. from +1 ft. to 19 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? ☐ Yes ☑ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☑ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
~~Bailer~~ Jet test 90 gal./min. with 109 ft. drawdown after 3 hrs.
Artesian flow 45 g.p.m.
Temperature of water Depth artesian flow encountered 109 ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 5 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Jackson Driller's well number
¼ ¼ Section 4 T. 35 R. 2W W.M.
Bearing and distance from section or subdivision corner 340' west 230' south from the north east property corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 109 ft.
Static level ft. below land surface. Date
Artesian pressure 16 lbs. per square inch. Date 8-31-70

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 120 ft. Depth of completed well 120 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Soil - Sandy - Brown	0	1	
Sandstone - Brown	1	12	
Sandstone - Grey	12	109	
Sandstone - Grey Broken	109	111	artesian
Sandstone - Grey	111	120	

Work started 8-31 1970 Completed 8-31 1970
Date well drilling machine moved off of well 8-31 1970

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Charles Gutierrez (Drilling Machine Operator) Date 9-10, 1970
Drilling Machine Operator's License No. 344

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Crater Well Drilling Inc. (Person, firm or corporation) (Type or print)
Address 1923 Delta Waters Rd. Med.
[Signed] (Water Well Contractor)
Contractor's License No. 83 Date 9-10

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45(