## WATER WELL REPORT STATE OF OREGON

5ACK 25 nc

## RECEIVED

JUL 9 1981 State Well No.

35 2W-12 de

WATER RESOURCES BEPPermit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Ernie Javier	County Jackson Driller's well number 514-1
Address 4258 Begal Road	SW 14 SE 14 Section 12 T. 35S R. 2W W.M.
City Wagle Point, State Or	Tax Lot # 415 Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location:
New Well   ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	4258 <b>BRAGUE</b> Kd.
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.  Static level ft. below land surface. Date 3
Rotary Air Driven Domestic Industrial Municipal	Artesian pressure lbs. per square inch. Date
Rotary Mud	(12) WELL LOG: Diameter of well below casing
	Depth drilled ft. Depth of completed well ft.
CASING INSTALLED: Steel Plastic Welded Welded Threaded Grant Fit. Gauge Communication of the Gauge Com	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
"Diam. from ft. to ft. Gauge	Sois Blown 01
	CLAY BROWN 1 4
(6) PERFORATIONS: Perforated? □ Yes ✓ No Type of perforator used	SANDSTONE BROWN 4 13
Size of perforations in. by in.	Smostone Blue 13 96
perforations from	50008 BLACK 96 98
perforations fromft. toft,	Jan087018 Blue 98 101 18
perforations from	SAND 80 E BLUE 101 133
(7) SCREENS: Well screen installed?   Yes P No	5000 500 E 30 E 133 134 18
Manufacturer's Name	3000 800 E 3 160
Type Model No.	
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft. to	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made?    Yes    No    If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
Air test gal./min. with drill stem at 60 ft. hrs.  Reiler test gal./min. with ft. drawdown after hrs.	
Butter cess	
Artesian flow g.p.m.  perature of water Depth artesian flow encountered ft.	
	Work started 3 198 Completed 189
(9) CONSTRUCTION: Special standards: Yes \( \subseteq \) No \( \subseteq \)	
Well seal—Material used	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision. Waterials used
Diameter of well bore to bottom of sealin.	and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Occupation Date Date 10.
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.
How was cement grout placed? LESSWIE CROWN	Diffing Machine Optical Statements.
Hantre Boton B	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and ballet.
Was pump installed? Type HP Depth ft.	Name 12 ES political Europe
Was a drive shoe used? ☐ Yes ☐ No Plugs	(Person, firm or exporation) (Type or print)
Did any strata contain unusable water?	Address Address
Method of sealing strata off	[Signed] Sem (Water Well Contractor)
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Contractor's License No Date 1981
Gravel placed from ft. to	, 1334