

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

JACK
34803

STATE OF OREGON
(Please type or print)

(Do not write above this line)

State Well No. 36S/3W-3560
State Permit No.

(1) OWNER:

Name Gary DelGrande
Address 5595 Kane Crk. Rd.
Central Point, Ore.

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Other Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

6 " Diam. from 0 ft. to 62 ft. Threaded Welded
Gage See #12
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? Yes No If yes, by whom?
D: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
AIR
Bailer test 20 gal./min. with 170 ft. drawdown after 1 1/2 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 35 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 12 sacks
How was cement grout placed? pressure grouted

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? Yes No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Jackson Driller's well number
SW 1/4 NW 1/4 Section 35 T. 36S R. 3W W.M.
Bearing and distance from section or subdivision corner
Tax lot-1603 Permit-746-79W

(11) WATER LEVEL: Completed well.

Depth at which water was first found 66 ft.
Static level ft. below land surface. Date 10/17/79
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 200 ft. Depth of completed well 200 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Clay--brown	0	30	
Granite--brown	30	53	
Granite--black	53	80	
Granite--green	80	120	
Granite--black	120	123	
Granite--green	123	200	30
62' 6" SDR 26(class 160) PST PVC NSF type 1120 ASTM 2241 installed.			
RECEIVED			
OCT 22 1979			
WATER RESOURCES DEPT. SALEM, OREGON			

Work started 10/17 19 79 Completed 10/17 1979
Date well drilling machine moved off of well 10/17 1979

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] *Thomas Driver* Date 10/18, 1979
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1242

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Virgle Gribble Well Drilling
(Person, firm or corporation) (Type or print)

Address 8380 Ramsey Rd., Gold Hill, Ore.

[Signed] *Virgle Gribble*
(Water Well Contractor)

Contractor's License No. 705 Date 10/18, 1979