NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

~ (Please type or print)

(Do not write above this line)

State Well No	36s/3w-35db
---------------	-------------

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Gary Webb	County Jackson Driller's well number
Address P. O. Box 3303,	NW 14 SE 14 Section 35 T. 36Sr. 3W W.M.
Central Point, Ore.	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Permit97-80W Tax lot1000
New Well 🖰 Deepening 🗌 Reconditioning 🗍 Abandon 🖂	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 52 ft.
Rotary 🔁 Driven 🗌 Domestic 🛣 Industrial 🗌 Municipal 🗎	Static level 6 ft. below land surface. Date 4/16/80
□ Bored □ Irrigation □ Test Well □ Other □	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded DX 6	(12) WELL LOG: Diameter of well below casing 6 Depth drilled 83 ft. Depth of completed well 83 ft.
ft. Gage ft. Gage	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
(6) PERFORATIONS: Perforated? ☐ Yes ☑ No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Soilbrown 0 8
perforations from ft. to ft.	Gravelmed. 8 21
perforations from ft. to ft.	Claystonebrown 21 50
perforations from ft. to ft.	Fractured rockbrown 50 79
(7) SCREENS: Well screen installed? □ Yes 咨 No	<u>Basaltblack</u> 79 83 6
Manufacturer's Name	
Type Model No	
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is	
lowered below static level	
Was a pump test made? ☐ Yes ☒ No If yes, by whom?	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
i: gal./min. with ft. drawdown after hrs.	AFR2 1 1980
	WATEL FLEOURCES DEPT
<u> </u>	CTCON
Bailer test 65 gal./min. with 77 ft. drawdown after $1\frac{1}{2}$ hrs.	
sian flow g.p.m.	Work started 4/16 19 80 Completed 4/16 1980
Semperature of water Depth artesian flow encountered ft.	
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4/16 1980
Well seal—Material used Cement	Drilling Machine Operator's Certification:
Well sealed from land surface to ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below seal	[Signed] Date 4/19, 180
How was cement grout placed? pressure grouted	Drilling Machine Operator's License No
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Kyes No Plugs Size: location ft.	Name Virgle Gribble Well Drilling
Did any strata contain unusable water? ☐ Yes ※ No Type of water? depth of strata	(Type or print) Address 8380 Ramsey Rd., Gold Hill, Ore.
	1. M. II A
Method of sealing strata off	[Signed] Lyg Illkand.
Was well gravel packed? ☐ Yes 🖺 No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 705 Date 4/19 , 19 ⁸⁰