NOTICE TO WATER WELL CONTRACTOR	< AC'00
The original and first copy of this report are to be filed with the	LL REPORT 35/2 w - 13
STATE ENGINEER, SALEM, OREGON 97310 MAY 21 1965 STATE OF Within 30 days from the datSTATE ENGINEER tyre of well completion.	
SALEM OPECON	(11) WELL TESTS. Drawdown is amount water level is
(1) OWNER: Name Glen Lowman	towered below static level
Address 3514 Navajo Way	Was a pump test made? ☐ Yes ▼ No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs
Las Vegas, Nevada	n n n n n n
(2) LOCATION OF WELL:	n n n n
(2) ECCATION OF WELL.	Bailer test 100 gal./min. with 13 ft. drawdown after 2 hrs
County Jackson Driller's well number	Artesian flow g.p.m. Date
½ ½ Section 13 T. 35S R. 2W W.M.	Temperature of water 56 Was a chemical analysis made? Yes XN
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing 6
	Depth drilled 165 ft. Depth of completed well 165 f
The second secon	
	Formation: Describe by color, character, size of material and structure, an show thickness of aquifiers and the kind and nature of the material in east stratum penetrated, with at least one entry for each change of formation
(3) TYPE OF WORK (check):	MATERIAL FROM TO
Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	Claydark brown010Sandstoneblue10165
bandonment, describe material and procedure in Item 12.	Sands tonebittle 10 105
(4) PROPOSED USE (check): (5) TYPE OF WELL:	
(4) PROPOSED USE (check): (5) TYPE OF WELL: Rotary X Driven	
Domestic Ki Industrial Municipal Cable Jetted	
Irrigation Test Well Other Dug Bored	
(6) CASING INSTALLED: Threaded □ Welded □	
6 " Diam, from 0 ft. to 2] ft. Gage 250	
"Diam. fromft. toft. Gage	
"Diam. fromft. Gage	
(7) PERFORATIONS: Perforated? ☐ Yes IXNo	
Type of perforator used	
Size of perforations in. by in.	
perforations fromft. toft.	
perforations fromft. toft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
perforations fromft. toft.	
(8) SCREENS: Well screen installed? Yes X No	
Manufacturer's Name	
Model No.	
Slot size Set from ft. to ft.	Work started May 12 1965 Completed May 14 196
Diam, Slot size Set from ft. to ft.	Date well drilling machine moved off of well May 15 196
(9) CONSTRUCTION:	(13) PUMP:
Well seal—Material used in seal Bentonite	
Depth of seal 21 ft. Was a packer used? 10	Manufacturer's Name
Diameter of well bore to bottom of seal in.	Type: H.P.
Were any loose strata cemented off? Thes No Depth	Water Well Contractor's Certification:
Was a drive shoe used? ☐ Yes ┺ No	This well was drilled under my jurisdiction and this report i
Was well gravel packed? Yes X No Size of gravel:	true to the best of my knowledge and belief.
Gravel placed fromft. toft.	NAME GRIBBLE & MILKOWSKI
Did any strata contain unusuable water? Yes No	NAME GRIBBLE & MILKOWSKI (Person, firm or corporation) (Type or print) Pt 2 Port / 97 (2) 3 Hall
Type of water? depth of strata	Address Rt. 2 Box 483, Gold Hill, Oregon
Method of sealing strata off	Drilling Machine Operator's License No87
(10) WATER LEVELS:	
Static level 12 ft. below land surface Date May 14	[Signed] (Water Well Contractor)
Artesian pressure lbs. Er square inch Date	Contractor's License No. 73 Date May 20 , 19 65
(USE ADDITIONAL SE	