## WATER WELL REPORT STATE OF OREGON

## RECEIED

JUL 2 1982

## WATER RESOURCES DEPT BALEM, OREGON

35385

X State Well No. 365/4W-15cb

State Permit No. .....

(1) OWNER:	(10) LOCATION OF WELL:		
Name City of ROGUE RIVER	County TACKSON Driller's well number		
Address 133 BROADWAY	SE 45W 4 Section 15 T. 365	"R. 4 W	W.M.
City ROGUE RIVER State OK. 97537	Tax Lot # Lot Blk	Subdivision	
(2) TYPE OF WORK (check):	Address at well location: PIDE St. B.	i-Cente	nniaL
New Well 🔥 Deepening 🗆 Reconditioning 🗆 Abandon 🗆			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF_WELL: (4) PROPOSED USE (check):	Depth at which water was first found 70		
Rotary Air A Driven Domestic Industrial Municipal	Static level 21 ft. below land surface. Date 5/25/82  Artesian pressure lbs. per square inch. Date		
Rotary Mud		r square inch. Date	· · · · · · · · · · · · · · · · · · ·
Bored   Thermal: Withdrawal  Reinjection	(12) WELL LOG: Diameter of well below	_	
(5) CASING INSTALLED: Steel Plastic Plastic	Depth drilled /// ft. Depth of completed well /// ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry		
8" Diam. from O ft. to 86 ft. Gauge 250			
	for each change of formation. Report each change in pand indicate principal water-bearing strata.	osition of Static W	ater Level
LINER INSTALLED:			
	MATERIAL DATE	From To	SWL
	BROWN CLAY	0 10	
(6) PERFORATIONS: Perforated? ☐ Yes No	BROWN CLAY COARSE GRAVEL & ROULDERS	10 30	
Type of perforator used		10 30	-
Size of perforations in. by in.	GRAYCIAY COARSE GRAVEL	33 112	
perforations from	E Bouldes	30 45	
perforations from ft. to ft.	LO. COARSE GRAVEL	45 90	
ft. toft.	FRACTURED BASAIT	90 100	-
(7) SCREENS: Well screen installed?   Yes XNo	-		
Manufacturer's Name			<del></del>
Type Model No.			x -
Diam. Slot Size Set from ft. to ft.			-
Diam. Slot Size Set from ft. to ft.			<del></del>
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
was a pump test made? ☐ Yes A No If yes, by whom?			
d: gal./min. with ft. drawdown after hrs.			
" " " "			
Air test 300 f gal./min. with drill stem at 7/ ft. / hrs.			<del></del> .
Bailer test gal./min. with ft. drawdown after hrs.			-
esian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started 5/24 1982 Complete	d 6/7	1982
(9) CONSTRUCTION: Special standards: Yes No M	Date well drilling machine moved off of well	6/2	19 82
Well seal—Material used CEMENT GROUT	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct st	upervision. Mate	rials used
Diameter of well bore to bottom of sealin.	and information reported above are true to my be	est knowledge an	nd belief.
Diameter of well bore below sealin.	[Signed] Charles B Peller	2. Date 6.	7, 19. <b>8.2</b>
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No		
How was cement grout placed? GROUT PUMP	Drining Machine Operator's Excense No		
	Water Well Contractor's Certification:		
n 0	This well was drilled under my jurisdiction and this report is true to		
Was pump installed?	the best of my knowledge and belief.  Name M. C. A.A. HAA. WE!! DRI!!!		
Was a drive shoe used?   Yes □ No Plugs Size: location ft.	(Person, firm or corporation)	(Type or	print)
Did any strata contain unusable water?	Address 141, N.E. BEACON DR. GRA	INTS PASS,	OR 47526
Type of Water? depth of strata	[Signed] Co. Wilanale	,	
Method of sealing strata off	(Water Well Contract	or) list	······
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	Contractor's License No	6.114	, 19 <b>8.Z</b>
Gravel placed from ft. to ft.	j		