NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

~57	•			
481	State Well No	<u>35s</u>	/zw	-23 b

.015	1
1. Qu	State Well No. 350 / zw - 23 kd
Ø	
	State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:				
Name Dale Lawrence	County Jackson Driller's well number				
Address 14051 Antioch Rd.	SE 14 NW 14 Section 23 T. 35S R. 2W W.M.				
Gentral Point, Ore.	Rearing and distance from section or subdivision corner				
(2) TYPE OF WORK (check):	Tax lot700 Permit162-80W		····		
New Well K Deepening Reconditioning Abandon					
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 42 ft.				
Rotary Driven Domestic X Industrial Municipal D	Static level 20 ft. below land s	urface. Date5/	5/80		
Cable ☐ Jetted ☐ ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date				
(5) CASING INSTALLED: Threaded Welded 6 " Diam from 0 ft to 40 ft GageSee#12	(12) WELL LOG: Diameter of well below casing6 Depth drilled 103 ft. Depth of completed well 103 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,				
6) PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.				
Type of perforator used	MATERIAL	From To	swL		
Size of perforations in. by in.	Soilbrown	0 2	.		
perforations from ft. to ft.	Claybrown	2 11			
perforations from ft. to ft.	Claystonebrown	11 16			
perforations from ft. to ft.	Claystonegray	16 71			
	" bkack	71 74			
(7) SCREENS: Well screen installed? Yes XNo.	gray	74 82			
Manufacturer's Name	black	82 85			
Type Model No.	gray	<u>£15 103</u>	20		
Diam. Slot size	11				
Diam. Slot size Set from ft. to ft.			+		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level					
a pump test made? Yes No H yes, by whom?		- 446			
gal./min. with ft. drawdown after hrs.	SDR 26 (class 160) PSI PVC NSI	Type 112			
Y	ASTM 2241		·		
"ATR " " "		1 71027	 		
Bailer test 85 gal./min. with 83 ft. drawdown after $1\frac{1}{2}$ hrs.		2.31000	`		
esian flow g.p.m.	THE A TOTAL OF A SECOND	SURCES D	EPT		
Emperature of water Depth artesian flow encountered ft.	Work started 5/5 180 Complete	ed 5/50N	19 80		
	Date well drilling machine moved off of well		19 80		
(9) CONSTRUCTION: Well seal—Material used Cement	Drilling Machine Operator's Certification:	<u> </u>			
Well sealed from land surface to	This well was constructed under my Materials used and information reported best knowledge and belief	direct supe above are tr	ue to my		
Diameter of well bore below sealin.	[Signed] (Drilling Machine Operator)	Date <u>5/.7</u>	, 1980.		
Number of sacks of cement used in well seal 7 sacks How was cement grout placed? Pressure grouted	Drilling Machine Operator's License No.	1242			
	Water Well Contractor's Certification:				
	This well was drilled under my jurisditrue to the best of my knowledge and bel		report is		
Was a drive shoe used? Yes Yo Plus Size: location ft.	Name Virgle Gribble Well Drilling				
Did any strata contain unusable water? Yes No Type of water? depth of strata	(Person, firm or corporation) Address 8380 Ramsey Rd., Gold 1	Type or r Hill, Ore.			
Method of sealing strata off	l'omill.	1.			
Was well gravel packed? [Yes K No Size of gravel:	[Signed] (Water Well Contr	actor)	************		
Gravel placed fromft. toft.	Contractor's License No. 705 Date 5	/7	1980		
	IPPTC IF NECECCADE				