## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

## WATER WELL REPORT

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECE STATE OF OREGON

Pleased pe or print)

(Do not write above this line)

cX	- 4 /	
SPCI	State Well No. 355/24	0-26
279	State Permit No.	
73°	300 1 CAME 110	-

JUL 1 1 1977	bove and me,		
(1) OWNER.	(10) LOCATION OF WELL:		
Name Josey Const WATER RESOURCES DEF	County Jack SOH Driller's well number		
Address 13325 Antiock SALEM, OREGON	14 14 Section 26 T. 35 R. 211 W.M.		
Central frint, Whe.	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivision corner		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	13325 Antiock		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 90		
Rotary Driven Domestic Industrial Municipal Domestic			
Cable	Static level 20 ft. below land surface. Date 6, 27		
	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing		
6 "Diam from #1 ft. to 23 ft. Gage 1250	Depth drilled 400 ft. Depth of completed well 400 ft.		
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;		
" Diam. from	and show thickness and nature of each stratum and aquifer penetrated		
PERFORATIONS: Perforated?   Yes   Z-No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	Transport v		
Size of perforations in. by in.			
perforations fromft. toft.	Claristan Grown 2 15		
perforations fromft. toft.	Sandstone - brown 15 22		
perforations from ft. to ft.	Sand-Tan= -6/11- 22 89		
/EV CCOPERIO	Clayston - Groken-ster 89 91 20		
(7) SCREENS: Well screen installed?   Yes No	Jandston-stey 91 198		
Manufacturer's Name	6asa/6 - 6Rectional 98 219 20		
Type Model No Diam Slot size Set from ft. to ft.	Syndstage - Stey 219 274		
Diam. Slot size Set from ft. to ft.	60501E - Wind 234362		
The state of the s	Sana 5/04 - Stey 362 311		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Dusall - 6/11/00 31/400		
Was a pump test made?  Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " "			
" " " "			
Bank test 6 gal./min. with ft. drawdown after / hrs.	w."		
perature of water Depth artesian now encountered	Work started 6 - 24 19 7 Completed 6 - 27 19 77		
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6-27 19 7		
Weil seal-Material used Comony	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and interpration reported above are true to my		
Diameter of well bore to bottom of seal in.	best knowledge and belief.		
Diameter of well bore below seal in.	[Signed] Lundon Date 627, 1877		
Number of sacks of cement used in well seal sacks	(Drilling to chine Operator)		
How was cement grout placed? TESSUF PUMP	Drilling Machine Operator's License No.		
The state of the s	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? ☐ Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water?  Yes	Name (Person, firm or corporation)		
Type of water? depth of strata	Address 923 Delta Material		
Method of sealing strata off	201		
Was well gravel packed? ☐ Yes ■ No Size of gravel:	[Signed] (Water Well Constactor)		
Gravel placed from ft. to ft.	2/1-6 2 2 2 2		
A Leady and the second	Contractor's License No. 20 Date		