NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date

RECEIVE STATE OF OREGON

. CK	· -	2//-	. 51
279	State Well No.	200/20	w-26
多()	State Permit 1	Yo	***************************************

of well completion. (Do not write a	bove this line)	
(1) OWNER: WATER DECOURGES 200	(10) LOCATION OF WELL:	
Name Josey Constitution DEP	County Jak Sold Driller's well no	ımher
Address 13325 Antico FALEM, CREGON	14 14 Section 26 T. 35	·
Central foint Ote		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on corner
New Well ☑ Deepening □ Reconditioning □ Abandon □	133	25 Antiock
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	90 ft.
Rotary Driven Domestic Dindustrial Municipal Domestic	Static level 20 ft. below land s	surface. Date 6 27-7
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per squar	e inch. Date
, CASING INSTALLED: Threaded Welded E	(12) WELL LOG: Diameter of well h	
6 "Diam from 11 ft. to 23 ft. Gage 1250	2/1	
ft. Gage ft. Gage		700
ft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each stratum	m and aquifer penetrated,
PERFORATIONS: Perforated? Tyes Plant	with at least one entry for each change of format position of Static Water Level and indicate prin	tion. Report each change in
ype of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Soil Brown	2 15
perforations from ft. to ft.	Claysian 6 60011	15 22
perforations from	Sand-Slane - Growth	22 88
	Mareton - Hoken-Ster	89 91 20
(7) SCREENS: Well screen installed? Yes No	Jandston stell	91 198
Manufacturer's Name	Gasalt - 6 Keeticker	198 219 20
Type Model No	Syndstagy - Strey	219 274
Diam. Slot size Set from ft. to ft.	Gasalt - Glist	22/362
Diam. Slot size Set from ft. to ft.	Sann Span - Sirey	36-6 36/
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	DUSAIL - ESTIPE	317 700
Was a pump test made? Yes A No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		
Bally shifts. Hold Is determined after man		
" " " "		
19/6		
Baffer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m.		
perature of water Depth artesian flow encountered	Work started 6-24 19 7 Complete	ed 6 -27 19 2
	Work started 19 Complete Date well drilling machine moved off of well	<u> </u>
(9) CONSTRUCTION:		<u> </u>
Well seal—Material used Cement	Drilling Machine Operator's Certification: This well was constructed under my	direct supervision
Well sealed from land surface toft.	Materials used and information reported	above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.	100 04
Diameter of well bore below seal in. Number of sacks of cement used in well seal sacks	[Signed] (Drilling Machine Operator)	Date 6 27 , 1927
How was cement grout placed?	Duilling Machine Orosatoula Linnas No.	747
From Gottom UP		
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdi true to the best of my knowledge and beli	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Chalet Well 1)	William Inte
Did any strata contain unusable water? Yes	(Person, firm or corporation)	(Type or) print)
Type of water? depth of strata	Address 923 Del Testilla	Les Kelalle
Method of sealing strata off	[Signed]	2000
Was well gravel packed? Yes No Size of gravel:	(Water Well Control	actor
Gravel placed from ft. to ft.	Contractor's License No. 5 5 Date	B-21, 197