NOTICE TO WATER WELL CONTRACTOR The original and first copy of the port of the copy of the

WATER RESOURCES DEPARTMENT CO C 1070

STATE OF OREGON

lease type or print)

State	Well	No.	355/2w-28a	4
2				1

SALEM, OREGON 97310	DE0 20 1910	(PI
within 30 days from the date	AUDCES	
	~^	

of well completion ATER RESOURCES DE Not write above this line)

State	Well	No.	1	<u>ب</u>	3 4.0	w	 <u> </u>
State	Perm	nit N	Ĭο.				

SALEM. OREGON		
(1) OWNER:	(10) LOCATION OF WELL:	
Name Sams Valley Elementary District 6	County Jackson Driller's well nu	ımber
Address451 N. 2nd.	NE 14 SE 14 Section 28 T. 35S	R. 2W W.M.
Central Point, Ore.	Bearing and distance from section or subdivision	on corner
(2) TYPE OF WORK (check):	-Tax lot 1100 Permit 761-78W	
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	38 ft.
Rotary Driven Domestic Industrial Municipal		urface. Date 12/20/78
Cable	Artesian pressure lbs. per square	
CASING INSTALLED: Threaded Welded K	(12) WELL LOG: Diameter of well b	elow casing 6
6" Diam. from .0	Depth drilled 300 ft. Depth of comple	
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size a	and structure of materials:
ft. toft. Gage	and show thickness and nature of each stratur with at least one entry for each change of format	m and aguifer penetrated.
PERFORATIONS: Perforated? Tyes A No.	position of Static Water Level and indicate prin-	cipal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Soilbrown	0 10
perforations fromft. toft.	Claystonebrown	10 15
perforations from ft. toft_	Claystone0-gray	15 50
perforations from ft. to ft.	Sandstonegray	50 85
(7) SCREENS: Well screen installed? [] Yes XI No.	Claystoneblack	85 90
(1) SCREENS: Well screen installed? Yes X No	Claystonegray	90 118
Type Model No.	Sandstonegray	11 8 300
Diam. Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
· · · · · · · · · · · · · · · · · · ·	;	
Was a pump test made? Yes X No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		
" " "	S No State to the Property of the Control of the Co	
ATR " " "		
Bailer test 30 gal./min. with 279t. drawdown after 1½ hrs.	2	
Artesian flow g.p.m.		
perature of water Depth artesian flow encounteredft.	Work started 12/20 1978 Complete	d 12/20 1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well	12/20 19 78
Well seal—Material used Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface toft_	This well was constructed under my Materials used and information reported	direct supervision.
Diameter of well bore to bottom of seal in.	best knowledge and belief.	endove are are to my
Diameter of well bore below seal	[Signed] Drilling Machine Operator)	Date 12/22 , 19 78
Number of sacks of cement used in well seal sacks How was cement grout placed? Prossure	Drilling Machine Operator's License No	483
now was cement grout placed?	- Posterior Discount Tion	
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdic true to the best of my knowledge and belie	ction and this report is ef.
Was a drive shoe used? Yes X No Plugs Size: location ft.	Name Virgle Cribble Well Drill	
Did any strata contain unusable water 🗌 Yes 🖫 No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address 8380 Ramsey Rd., Gold H	Ill, Ore.
Method of sealing strata off	[Signed] Jan 2 Millson	oh.
Was well gravel packed? [] Yes No. Size of gravel:	(Water Well Contra	
Gravel placed from ft.	Contractor's License No. 705 Date 12	2 <u>/22</u> , 19.78