

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.
Corrected by WRD staff

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. 35S/2W-29bc

State Permit No. _____

(1) OWNER:

Name Roy L. Carver

Address 622 McDonough Rd.

Gold Hill, Ore.

(2) TYPE OF WORK (check):

New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Jetted ☐
Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

PLASTIC
Threaded ☐ Welded ☐

6" Diam. from 0 ft. to 20 ft. Gage See #12

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Is a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

ATR " " "

Filter test 140 gal./min. with 125 ft. drawdown after 1 1/2 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 6 sacks
How was cement grout placed? pressure grouted

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Jackson Driller's well number

SW SE 1/4 NW 1/4 Section 29 T. 35S R. 2W W.M.

Bearing and distance from section or subdivision corner

Tax lot--3605 Permit--378-80W

(11) WATER LEVEL: Completed well.

Depth at which water was first found 91 ft.

Static level 20 ft. below land surface. Date 8/22/80

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 145 ft. Depth of completed well 145 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil--brown	0	4	
Sandstone--brown	4	10	
Sandstone--gray	10	130	
Sandstone--pink	130	140	
Sandstone--gray	140	145	20
SDR26 (class 160) PSI PVC NSF type	1120		
ASTM 2241			

RECORDED

SEP 05 1980

WATER RESOURCES DEPT
SALEM, OREGON

Work started 8/22 19 80 Completed 8/22 19 80

Date well drilling machine moved off of well 8/22 19 80

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief

[Signed] Sammy Quinn Date 8/25, 19 80
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1242

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Virgle Gribble Well Drilling
(Person, firm or corporation) (Type or print)

Address 8380 Ramsey Rd., Gold Hill, Cr.

[Signed] Virgle Gribble
(Water Well Contractor)

Contractor's License No. 705 Date 8/25, 19 80