NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the SEP 7 - 1972 STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 ENGINEER type or print) within 30 days from the date I A I E ENGINEER type or print) of well completion. SALEM. OF Co not write above this line)

TAC	State Well No. 355/4W-10	c.
4935	State Permit No.	
(-		

(1) OWNER:	(10) LOCATION OF WELL:
Name K. S. Johem)	County Jackson Driller's well number 260
Address 888 E. Evans Co. Rd.	NW. 4 S4), 4 Section 10 T. 35 SR. 4 W. W.M.
Wimen, Bregon	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 38 ft.
Rotary Driven Domestic X Industrial Municipal D	Static level ft. below land surface. Date 64-72
Cable Jetted Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded K	(10) WHEN I LOCK
"Diam. from oft. to co ft. Gage 1250	(12) WELL LOG: Diameter of well below casing
	Depth drilled 60 ft. Depth of completed well 60 ft.
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
" Diam, from It. to It. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Tolca	MATERIAL From To SWL
Size of perforations (// in. by 4 in.	GREGETHE SAND 0 6
	" (COARSE GOSUEL BOUNDER L 45
18 perforations from 53 ft. to 59 ft.	DROMASON BOMALTE 15-60 5
perforations from	CRUMBESTS STATE AS 60 S
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? Yes No	
Monufacturar's Name	
Type Model No	1
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft.	-
Diani	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	-
Was a pump test made? ☐ Yes ☑ No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	M
<i>II II</i> , <i>II</i>	The state of the s
	2 Acres 28 () 1 March 197 Acres 197 () 199 () 1 March 197 () 199 () 1 March 197 () 1 Mar
75 10 4	
Bailer test /5 gal./min. with 10 ft. drawdown after 32 hrs.	. Programme and the second of
Artesian flow g.p.m.	
inperature of water 6 Depth artesian flow encountered ft.	Work started 5/29 1972 Completed 6/2 1972
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6/2 197
Well seal-Material used	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below sealin.	[Signed] - All Washine Operator) Date 9 5, 19
Number of sacks of cement used in well seal sacks	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 260
Brand name of bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Calana de la la II De Illiano
Did any strata contain unusable water? Tyes No	Name Coleman S Del Drilling (Person, firm or corporation) (Type S print)
	Address 2060 Vine, Grants Pass, Ove
Method of sealing strata off	[Signed]
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Gravel placed fromft.	Contractor's License No. 380 Date 9-5, 192-