NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

## WATER WELL REPORT

STATE OF OREGON

STATE ENGINEER, SALEM, ORECOMENTAL WITHIN 30 days from the date of well completion.

JUNS - 1972 Bease type or print)
(Do not write above this line)

State Permit No. .

	<del> </del>
(1) OWNER: SALEM. ORLSON	(10) LOCATION OF WELL:
Name K.S. JOKEM	County ACKS ON Driller's well number
Address 888   EAST EVANT CR. RD - WIMEN	NW 115E 1/2 Section T. 16 R. 355 44W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 58 ft.
Rotary   Driven   Domestic   Industrial   Municipal	Static level 5 ft. below land surface. Date 6-(-72
Cable   Jetted	Artesian pressure   Ibs. per square inch. Date
CASING INSTALLED: Threaded   Welded   Welded   Welded   Gage   CO	(12) WELL LOG: Diameter of well below casing
	Formation: Describe color, texture, grain size and structure of materials;
ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
) PERFORATIONS: Perforated? X Yes  No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used TORUH	MATERIAL From To SWL
Size of perforations //A in. by 4 in.	FINE SAND 06
18 perforations from 53 ft. to 59 ft.	TOARE GRAVET SUTTERED 6 45
perforations fromft. toft.	Rocks-
•	BECOMPOSED GAMITE 45 60 5
perforations fromft. toft.	GEOMINE POSITION OF S
(7) SCREENS: Well screen installed? ☐ Yes ✓ No	
Manufacturer's Name	
Type Model No.	
Diam Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	21.
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes K No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	The state of the s
" " " " " " " " " " " " " " " " " " " "	
Bailer test 29 gal./min. with 10 ft. drawdown after 7 hrs.	
Artesian flow g.p.m.	
nperature of water Depth artesian flow encounteredft.	Work started 5-29 19 72 Completed 6-2 19 72
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6 - 2 1972
Well seal-Material used	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal,in.	best knowledge and belief.
Diameter of well bore below seal	[Signed] G W Willem Date 5 , 1972
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)  Drilling Machine Operator's License No. 760
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.
Brand name of bentonite	Water Well Contractor's Certification;
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water lbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name DLEMAUZUELL DDILLING
Did any strata contain unusable water?   Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 2060 VINE - CLANTS PARS
Method of sealing strata off	[Signed] Joseph & Column
Was well gravel packed?   Yes No Size of gravel:	(Water Well Contractor)
Gravel placed fromft.	Contractor's License No. Date 6 7 19 72