Amended 11/12/2024 STATE OF OREGON

WATER SUPPLY WELL REPORT (as required by ORS 537.765)

Instructions for completing this report are on the last page of this form

JACK 56573

WELL ID # L 68223

(START CARD) # 161945

(1) OWNER: Well Number: 68223				(9) LOCATION OF	WELL by legal des	scriptio	n:	ongitude		
Name Ralph George Address P.O. Box 715 City Ashland State OR Zip 97520			Township 39S	N or S. Range <u>1</u> NW	E 1/4 N	E or	W. of W			
		Oute OR 2	P 31320		Lot Block ell (or nearest address) 2		Subdivi			
(2) TYPE OF W				Street Address of We	on (or riealest address)	925 MW	y 00			
X New Well	DeepeningAlte	eration (repair/recondition)	Abandonment	(10) STATIC WAT	FRIEVEL:					
(3) DRILL MET X Rotary Air	HOD: Rotary Mud	Cable	FA ft. below land surface. Date 10/29/2003 Artesian pressure 10 lb. per square inch. Date 10/29/2003							
Other				(11) WATER BEA	RING ZONES:					
(4) PROPOSE	USE:			Depth at which water						
Domestic Community Industrial Irrigation Thermal Injection Livestock Other			From To Estim			ited Flow	Rate	SWL		
(5) BORE HOL	E CONSTRUCT		330	366	366 20			FA		
	approval Yes	XNo Depth of Comp	oleted Well 380 ft.							
Explosives used	Yes X No Type	SEAL Amo	Amount			<u></u>				
Diameter From		erial From To	sacks or pounds	(12) WELL LOG:	Ground ele	vation				
10 0	39 Bentonite	e 2 0 39	15 sacks							
6 39	380			Top soil Decomposed granit		1	From 0	To 2	SWL	
							2	33		•
				Brown siltstone			33	330		
How was seal place	d: Method \[\] A	B C D	T _F	Broke brown claystone			330	380	FA	
X Other Poured					RECEIV	ED	=			
Backfill placed from		ft. Material			TIEOLIV					
Gravel placed from		ft. Size of gravel			DEC 122	บบว				
(6) CASING/LII	NER:				DLO 1 4 2	UUJ				
Diameter	1 . 1	<u> </u>	Welded Threaded		WATER RESOURCE	S DEP	т —			
Casing: 6	+1 39	.250 X			SALEM, OREC					
					ACLIFANTA POHI I IN	~ IAIC	_ D		=11/	~ n
Liner: 4 5 380 SDR26 X X			ASHLAND DRILLING INC			RECEIVED			ΞIJ	
Final location of sho	e(s)			600 South Pacific Hwy				50 0		
(7) DEDECIDAT	TIONS/SCREEN	16.	Talent, OR 97540			L	EC 2	2	. 3	
Perforations		40.			541-488-2827	,	MATE	RRES	OURCE	e are
X Screens	Type Fac	tory Material	PVC		<i>₩</i> (*400-202/				OREG	
	Slot	Tele/pipe		Driller Comment	: Bentonite seal wa	s left				,
From To 320 340	size Number	Diameter size 4 SDR21	Casing Liner	down 2 ft. to leav	ve room for pitless					
360 380	1/16	4 SDR21						L	L	
				Date started 10/29/2003						
				1 '	Well Constructor Cert performed on the constru			abandon	ment	
				1	nce with Oregon water sup					
(8) WELL TES	TS: Minimum t	esting time is 1 ho	ur		mation reported above are					
Pump	Bailer	XAir	Flowing Artesian	belief.	- 2	1404	VO N	404	_	
Yield gal/min	Drawdown	Drill stem at	Time	Signed (Show		e 12/2 /	^{per} 181 2003	9	
20	380	380	1 hr.	Asilland Dr	illing Inc					
20	300			(bonded) Water We	II Constructor Certific					
				I accept responsibility	for the construction, altera	ation, or a				
Tomporet == cf\4/-	hr 50	Conth Artacian Flour formed			luring the construction date				K	
Temperature of Wa Was a water analys		Depth Artesian Flow found By whom		performed during this time is in compliance with Oregon water supply well construction standards. This repert is true to the best of finy knowledge and belief.						
•	ain water not suitable]Too little		1/2/18	//w	VC Numl	per 147	8	
	ly Odor C	olored Other		Signed	110 X4	Dat	e 12/2/	2003		
Depth of strata:				Ashland Dr	niling inc.					