WATER WELL REPORT STATE OF OREGON

RECEIVED

JUL 1 1981

	36/14/20	
	445-36	aa
State Well No.	7	********

WATER RESOURCES DEPT

State Permit No. SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Mike HuwT	County Jackson Driller's well number 81-28
Address 135 tary Valley Rd. #57	4 4 Section 36 T. 1W R. 5 W.M.
City Madford O State ORE	Tax Lot # 200 - Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: LYNN Rd Eagle Poin
New Well Deepening □ Reconditioning □ Abandon □	(44) WARRED I FOREST Commission of the design of the second
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
	Depth at which water was first found 6 ft.
(6)	Static level 19 ft. below land surface. Date 6 25
Rotary Air 2 Driven	Artesian pressure lbs. per square inch. Date
Rotary Mud	(12) WELL LOG: Diameter of well below casing
CACING DICTALLED.	Depth drilled 122 ft. Depth of completed well 122 ft.
CASING INSTALLED: Steel Plastic Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show
8	thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level
"Diam. from	and indicate principal water-bearing strata.
▲ LINER INSTALLED:	MATERIAL From To SWL
	clay Brown 0 8
"Diam. fromft. toft. Gauge25	0.50
(6) PERFORATIONS: Perforated? ♥ Yes □ No	Claystone Blue 25 52
Type of perforator used 5K1LL Saw	Share Rock Blue 52 62 19
Size of perforations 4 in. by in.	Shalo Rock, Frac-
283 perforations from .1.22 ft. to .62 ft.	TURED, Blue AND 62 91
perforations from	GOEY
perforations from ft. to ft.	SHALE ROCK 91 114
(7) SCREENS: Well screen installed? Yes No	SHITE NOVE
Manufacturer's Name	SHALE ROCK Fract
Type Model No	TURED RIVE AND 114 122
Diam. Slot Size Set from ft. to ft.	CEFU
Diam. Slot Size Set from ft. to ft.	ORE 7
Drawdown is amount water level is lowered	
(8) WELL TESTS: below static level	
Was a pump test made? ☐ Yes ☐ Yes, by whom?	
ield: gal./min. with ft. drawdown after hrs.	
n n	
Air test 50 gal./min. with drill stem at 121 ft. 3/2 hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Imperature of water Depth artesian flow encountered ft.	Work started 6-19 198 Completed 6-23 1981
CONSTRUCTION: Special standards: Yes No	Date well drilling machine moved off of well 6-23 198
Well seal—Material used CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of sealin.	and information reported above are true to my jest knowledge and belief.
Diameter of well bore below sealin.	[Signed]
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No
How was cement grout placed?	Drining Wachine Operator's Elicense No
PRESSURE GROUT	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to
Was pump installed? Type HP Depth ft.	the best of my knowledge and belief.
Was a drive shoe used? ☑Yes ☐ No Plugs Size: location ft.	Name OTUDERITE (Type or print) (Type or print)
Did any strata contain unusable water? Yes	Address 4876 Hyw 66 HShland
Type of Water? depth of strata	John Stortelake
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed? ☐ Yes 11 No Size of gravel:	1 V 2
Gravel placed from ft. to ft.	