NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT.

SALEM, OREGON 97310 within 30 days from the date of well completion.

AUG 61979 (Please type or print)
(Do not write above this line)

State	Well No. 365/1W-2)
State	Permit No

WATER RESOURCES DEPT		
(1) OWNER:	(10) LOCATION OF WELL:	
Name: DESERT MOBIL ESTATE	County ACKSON Driller's well n	umber 61-79
Address 2821 BULLOCK RD	14 14 Section 2/A T. 36	
MEDFORD, ()R	Bearing and distance from section or subdivis	
(2) TYPE OF WORK (check):		EC4297#
New Well Deepening Reconditioning Abandon	WHITE CITY, OR	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	69 ft.
Rotary Driven Domestic Industrial Municipal Domestic	Static level 6 ft. below land	· /
Bored Irrigation Test Well Other		re inch. Date
CASING INSTALLED: Threaded I Wolded		/ //
CASING INSTALLED: Threaded Welded St. Diam. from 72 ft. to 38 ft. Gage 350	(12) WELL LOG: Diameter of well	pelow casing 6
"Diam. fromft. toft. Gage	Depth drilled 6 ft. Depth of compl	eted well /80 ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size	and structure of materials;
	and show thickness and nature of each stratu with at least one entry for each change of forma	tion. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	SOIL-BROWN	03
perforations from ft. to ft.	CLAY-BROWN	
perforations from ft. to ft.	W/ GRAVEL	3.10
perforations from	CLAY-BROWN	16 33
(7) SCREENS: Well screen installed? Yes Ano	STANDSTONE-BROWN!	33 6/
Manufacturer's Name	SANDSIONE - GREY	6/69
Type Model No	SANDSVONE BULL	19 -70 10
Diam Slot size Set from ft. to ft.	SANDSTANE- PLUE	170 98
Diam. Slot size Set from ft. to ft.	SANDSTANE-GREY	98 141
(8) WELL TESTS: Drawdown is amount water level is	CLAYSTONE-BROWN	
lowered below static level	Y BROKEN	141 142 10
Was a pump test made? Yes No If yes, by whom?	SANDSTONE - GREY	142 157
gal./min. withft. drawdown after hrs.	CILAYSTONE - BLACK	157/60 10
" " " " " " " " " " " " " " " " " " "	SANDSTONE-GREY	160 180
TET " " "		
gal./min. with 50ft. drawdown after hrs.		
Artesian flow g.p.m.		
mperature of water Depth artesian flow encountered ft.	Work started 7-30 1979 Complete	·フー 30-19フタ
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7-30 -1975
Well seal—Material used	Drilling Machine Operator's Certification:	/
Well sealed from land surface to	This well was constructed under my	direct supervision
Diameter of well bore to bottom of sealin.	Materials used and information (eported best knowledge and belief)	above are true to my
Diameter of well bore below seal in.	[Signed]	7-30.79
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	rate
How was cement grout placed?	Drilling Machine Operator's License No	100
E	Water Well Contractor's Certification:	_
	This well was drilled under my jurisdic	tion and this
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and bell	f and this report is
Did any strata contain unusable water? \(\text{Yes} \) No	Name CRATER OFLL	JRILLING-LA
Type of water? depth of strata	(Person, firm or corporation) Address	(Type or print)
Method of sealing strata off	Address	THUY
Vas well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed])
Gravel placed from	Contractor's License No.	79
- August	WOLLD STOPPING NOTE IN The Asset Ass	May 2 7 5 5 Warm 1 1 1 1 1 1 1