## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

## WATER WELL REPORT

## STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 (Please type or print) within 30 days from the data.

(Please type or print) (

JACK 10991	State Well No. 36s-2w-18
	State Well No. 365-2w-18 State Permit No.

of well completion.	pove this line)
(1) OWNER: NOV - 4 1975	(10) LOCATION OF WELL:
WATER RESOURCES DEPT	County COC SON Driller's well number
C SAV FM - OREGON	W 1/2 NE 1/2 Section / 8 T360 R. ZW W.M.
Address OSSO DOCTORIONALISMO	
	Bearing and distance from section or subdivision corner
New Well	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found
Rotary Driven Domestic Dindustrial Municipal	Static level 3 ft. below land surface. Date 10
Cable	Artesian pressure lbs. per square inch. Date
CACINIC INCOMINED.	6
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing
C" Diam. fromft. toft. Gage 1.250	Depth drilled 60 ft. Depth of completed well 45 ft.
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
ft. Gageft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated?   Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
	Clay 5000 A 50ft 08
Size of perforations in. by in.	amuel medium losse 8 19
perforations fromft_ toft.	Clay heavy, impervious 19 30,
perforations fromft. toft.	gravel medium clay 30 34
perforations fromft. toft.	sandstone, med hand 34, 44
(7) SCREENS: Well screen installed? \( \subseteq \text{Yes} \)	stravel, losse, water baning 44 60 13
Manufacturer's Name	-11-00-0-1
TypeModel No	
Diam. Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
ON WIFT TERMS. Drawdown is amount water level is	
lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" "	
.".0	
Bailer test 45 gal./min. with 7 ft. drawdown after / hrs.	
Artesian flow g.p.m.	
	Work started 10/24 1975 Completed 10/28 1975
perature of water Depth artesian flow encountered ft.	12/10
(9) CONSTRUCTION:	Date well drilling machine moved off of well
Well seal-Material used Sement grout	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief
Diameter of well bore below seal	[Signed] [Signed] [Signed] [Maskin Date   430, 19
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal	Drilling Machine Operator's License No.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water lbs./100 gals.	true to the hest of my knowledge and belief
Was a drive shoe used? Yes No Plugs Size: location ft.	Name M Clanaran Well Killing
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address T NA Cuffy Control of the Co
Method of sealing strata off	[Signed] May Thurk
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Controtor)
Crevel placed from # to	Contractor's License No. 014 Date 10/5/