RECEIVED
AUG 31 1962
STATE ENGINEER
SALEM, OREGON

JACK 702

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON, within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

State Well No. 34/1W-15

State Permit No.

(1) OWNER:
Name ATHEL DUDLEY
Address P.O. Box 44
SHADY COVE, ORE.

(2) LOCATION OF WELL:
County JACKSON Driller's well number 1022
¼ ¼ Section 15 T. 34S R. 1 W.M.
Bearing and distance from section or subdivision corner
WEST SIDE, CRATER LAKE Hy
2. NORTH, OF ROGUE RIVER
BRIDGE.

(3) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED:
Threaded ☒ Welded ☐
6" Diam. from 0 ft. to 35 ft. Gage 0.25
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(7) PERFORATIONS:
Perforated? ☐ Yes ☒ No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS:
Well screen installed ☐ Yes ☒ No
Manufacturer's Name
Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:
Well seal—Material used in seal Cement & Bentonite
Depth of seal 35 ft. Was a packer used? No
Diameter of well bore to bottom of seal in.
Were any loose strata cemented off? ☒ Yes ☐ No Depth
Was a drive shoe used? ☒ Yes ☐ No
Was well gravel packed? ☐ Yes ☐ No Size of gravel:
Gravel placed from ft. to ft.
Did any strata contain unusable water? ☒ Yes ☐ No
Type of water? surface Depth of strata 20
Method of sealing strata off Cement & Bentonite
Perforated Drove 5 ft in Bedrock.

(10) WATER LEVELS:
Static level 20 ft. below land surface Date Aug 29/62
Artesian pressure lbs. per square inch Date

(11) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 10 gal./min. with 75 ft. drawdown after 1 hrs.
Artesian flow g.p.m. Date
Temperature of water 54 Was a chemical analysis made? ☐ Yes ☒ No

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 115 ft. Depth of completed well 114 ft.
Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Yellow Bouldery Gravel	0	30
Gray Claystone	30	65
White Claystone	65	71
Blue Claystone	71	105
Hard Basaltrock	105	115

Work started 8/20 1962 Completed Aug 29 1962
Date well drilling machine moved off of well Aug 29 1962

(13) PUMP:
Manufacturer's Name
Type: H.P.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME DEISTER'S WELL DRILLING CO.
(Person, firm or corporation) (Type or print)
Address P.O. Box 141 SHADY COVE ORE
Drilling Machine Operator's License No. 73
[Signed] Ray Deister
(Water Well Contractor)
Contractor's License No. 82 Date Aug 29, 1962

(USE ADDITIONAL SHEETS IF NECESSARY)