NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 (within 30 days from the date of well completion.

WATER WELL REPORT CEIVED State Well No. 365 2W27

(Please type or p

<i>V</i>	(Please type or print)	APR 1 C 1976	State Permit	No.	
(D	o not write above this line			•	

	SALEM, OF EGON
1) OWNER:	(10) LOCATION OF WELL:
(0000.3	County Driller's well number
ddress (385 Hersey ZEE W.	1/4 Section 27 T. 36, R. S.W. W.M.
ddress DECOCO	Bearing and distance from section or subdivision corner 7.5
2) TYPE OF WORK (check):	360' (1) at THE S.F. PROPERTY
	Chartel
Tew Well Deepening □ Reconditioning □ Abandon □  f abandonment, describe material and procedure in Item 12.	(dd) YVA MED Y DYDI - Completed and I
	(11) WATER LEVEL: Completed well.
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 1 ft.
Rotary Driven Domestic Industrial Municipal Domestic	Static level 9 ft. below land surface. Date 7/4/11/16
Oug □ Bored □ Irrigation □ Test Well □ Other □	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(10) THEFT LOC
CASING INSTALLED: Threaded Welded For the St. To Gage 1250	(12) WELL LOG: Diameter of well below casing
·	Depth drilled ft. Depth of completed well ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes   No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
	Sour Son GRAVEN Blown 0 1
Size of periode de la companya de la	CLAY LE GROVE Blown 1 3
perforations from 34 ft. to 34 ft.	CLAY Blown 3 9
perforations from ft. to ft.	CLAY LG GRAVEL DROWN 9 12
perforations fromft, toft.	(LA4 Blow) 12 24
(7) SCOPENS.	
(7) SCREENS: Well screen installed?   Yes No	CLAY-LG GRAVEL- SANDY BROWN 34 40 19
Manufacturer's Name	SANOY BLOWN ST 4017
TypeModel No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
lowed a second second	
Was a pump test made?   Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" "	
" " " " " " " " " " " " " " " " " " "	
Bailer test 26 gal./min. with 21 ft. drawdown after hrs.	
The state of the s	4
Artesian flow g.p.m.  Depth artesian flow encountered ft.	Work started 7 HPAIL 1976 Completed 7 HMIL 1976
perature of water Depth artesian now encountered	7/
(9) CONSTRUCTION:	Date well drilling machine moved off of well 747811 19/6
Well seal-Material used CEMESS	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.  Materials used and information raported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of wear sore to senting	[Signed] Eley Ol and Dave Helly)
Diameter of well bore below seal in.  Number of seeks of gement used in well seal sacks	(Drilling Machine Operator)
Number of sacks of cement used in well seal sacks  Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.
Brand name of bentonite  Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
The /100 dele	This well was drilled under my jurisdiction and this report is
of water	true to the best of my knowledge and belief.
Did any strata contain unusable watery \( \text{Ves} \) \( \text{Ves} \)	Name (Person, firm or corporation) (Type or print)
	Address 1923 Delta Waters Rd Medan
Type of water? depth of strata	TIME COD AND AND AND AND AND AND AND AND AND AN
Method of sealing strata off	[Signed] Charles V Conchooo
Was well gravel packed?   Yes   No Size of gravel:	(Water Well Contractor)
Gravel placed fromft,	Contractor's License No. 3.23. Date 7-8, 19.28
(USE ADDITIONAL S	HEETS IF NECESSARY) SP*45656-119