NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON REGION RE

, , , , , , , , , , , , , , , , , , ,	T. S. T. S. Miller State State, State Stat
(1) QWNER:	(10) LOCATION, OF, WELL:
Name Double DE Jumbs Q &	County Peleson Driller's well number
Address 711 BLOCK WELL ROLL	14 14 Section 38 T. 3(R. 3 W.M.
CENTRAL PR. OREGON	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	443 8 720 8 0 4 THE
New Well	N.W. PRUPERTY CORRER
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 9.2 / ft.
Rotary Driven Domestic Industrial Municipal	
Cable	Static level 5 6 ft. below land surface. Date Helical
The state of the s	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing
"Diam from the ft. to 6.4 ft. Gage 1.350	Depth drilled 160 ft. Depth of completed well 160 ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated?   Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Sow Beaut 01
perforations from ft. to ft.	CLAY SANOY BROWN 0 3
perforations fromft. toft.	CLAY Blown 3 6
perforations fromtt. tott.	CLAY LG. GLANGE BLOUR 6 8
(F) CODERAIC.	CLAY Bloun 8 37
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	CLAY LG GRAVEL Blown 37 44
Manufacturer's Name	Stown 3457
Diam. Slot size Set from ft. to ft.	C144 5400 Blum 57 53
Diam. Slot size Set from ft. to ft.	CHAY LC GLAVET BLOUN 53.58
(0) YVIII Y MYSOLIO Drawdown Is amount water level in	CLAYSTONE BLUE 69 95
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	SANDSTONE BLOKEN BLUE 92 95 56
Was a pump test made?   Yes No If yes, by whom?	CLAYSTONE BUF 95 1/3
Yield: gal./min. with ft. drawdown after hrs.	CLAYSTONE BLOKEN BLUE, 113 117 ST
" " " " " " " " " " " " " " " " " " "	CLAYSION MANUA 117 127
" " "	CANYSIONE DUE 12/160
Bailer test 5 gal./min. with 6 ft. drawdown after hrs.	
Artesian flow g.p.m.	
erature of water Depth artesian flow encountered ft.	Work started 7 HORIL 1976 Completed 7 HORIL 176
(9) CONSTRUCTION:	Date well drilling machine moved off of well 7 APRIL 196
Well seal-Material used CFn En	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] they along Date 7 4PRILIDE
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.
Number of sacks of bentonite used in well well sacks	Diming Machine Operator's License No.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 allons of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ✓ Yes ☐ No Pluss Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? ☐ Yes ☐ No	Name (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 1923 Delta Waters Rd Mellow
Method of sealing strata off	som the selection of the
Was well gravel packed?   Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed fromft toft.	Contractor's License No. 543 Date 4-8 , 1976
	, 10.72