NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
JUL 31 1975
WATER RESOURCES DEPT.
SALEM, OREGON

WATER WELL REPORT

STATE OF OREGON (Please type or print) JACK 8898 (Do not write above this line)

State Well No. 36S/3W-24

State Permit No.

(1) OWNER:

Name Byron Johnson

Address P. O. Box 162, Gold Hill, Ore.

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven []
Cable [] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal []
Irrigation [] Test Well [] Other []

CASING INSTALLED:

Threaded [] Welded [X]

6 " Diam. from 0 ft. to 21 ft. Gage 250

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? [] Yes [X] No.

Type of perforator used

Size of perforations in. by in.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

" AIR " " "

Bailer test 20 gal./min. with 100 ft. drawdown after 1½ hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement

Well sealed from land surface to 20 ft.

Diameter of well bore to bottom of seal 10 in.

Diameter of well bore below seal 6 in.

Number of sacks of cement used in well seal 4 sacks

Number of sacks of bentonite used in well seal sacks

Brand name of bentonite

Number of pounds of bentonite per 100 gallons of water lbs./100 gals.

Was a drive shoe used? [] Yes [X] No Plugs Size: location ft.

Did any strata contain unusable water? [] Yes [X] No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? [] Yes [X] No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Jackson Driller's well number

¼ ¼ Section 24 T. 36 R. 3W W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 97 ft.

Static level 3 ft. below land surface. Date 7/24/75

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 105 ft. Depth of completed well 105 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Soil--brown	0	5	
Granite--gray	5	97	
Granite--white	97	99	
Granite--gray	99	105	

Work started 7/24 19 75 Completed 7/24 19 75

Date well drilling machine moved off of well 7/24 19 75

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Lyz Milkowski (Drilling Machine Operator) Date 7/30, 1975

Drilling Machine Operator's License No. 483

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Gribble Well Drilling (Person, firm or corporation) (Type or print)

Address 8380 Ramsey Rd., Gold Hill, Ore.

[Signed] Wayne Milkowski (Water Well Contractor)

Contractor's License No. 461 Date 7/30, 19 75

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119