NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

· sock	State Well No. 365/3W-27b	
2106	State Well No. 36813W-21b	·(
4100	State Permit No.	

(1) OWNER:	(10) LOCATION OF WELL:
Name E. C.Brittsan	County Jackson Driller's well number
Address 5394 Teresa Way	SW 14 NW 14 Section 27 T. 36S R. 3W W.M.
Central Point, Ore.	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	tax lot-1602 Permit 552-79W
New Well	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 130 ft.
Rotary Driven Domestic Industrial Municipal	Static level 20 ft. below land surface. Date 8/14/79
Cable	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded H. S. "Diam. from 0 ft. to 119 ft. Gage 250 ft. to ft. Gage	(12) WELL LOG: Diameter of well below casing
Type of perforator used	MATERIAL From To SWL
Elle of positive and a second	-301101ack
perforations fromft. toft.	Clay & gravel brown med. 50 144
perforations from ft. to ft	Basaltblack 144 155
perforations from	Quartzwhite 155 157
(7) SCREENS: Well screen installed? ☐ Yes ☒ No	Basaltblack 157 300 20
Manufacturer's Name	
Type Model No.	
Diam. Slot size	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED
Was a pump test made? ☐ Yes 🔼 No If yes, by whom?	AUC 1 7 1979
Yield: gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT
" "	SALEM. OREGON
ÄTR " "	JALLIN. OKLOOK
Bailer test 30 gal./min. with 280ft. drawdown after $1\frac{1}{2}$ hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 8/13 1979 Completed 8/14 1979
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8/14 1979
Well seal—Material used Cement Well sealed from land surface to 40 ft. Diameter of well bore to bottom of seal 12 in. Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal 14 sacks How was cement grout placed? pressure grouted	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief: [Signed Corilling Machine Operator) Drilling Machine Operator's License No
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? MYes ☐ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes 🛛 No	Name Virgle Cribble Well Drilling (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 8380 Ramsey Rd., Gold Hill, Ore.
Method of sealing strata off	1. Marila 1
	[Signed] (Water Well Contractor)
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	1
Gravel placed from ft. to ft.	Contractor's License No. 70.5 Date